

Frameless Lightweight Safety Glasses

Billings® ANSI CSA



Anti-Fog



Scratch Resistant



Ultraviolet Protection

FEATURES

Rubber temple tips
Lightweight frameless design
Wraparound coverage

CAPTURE CLAM

MODEL NO. STYLE NO.

EB171 CH110STCS ● Clear Anti-fog

EB172 CH120STCS ● Gray Anti-fog

POLYBAG

MODEL NO. STYLE NO.

EB110 CH110S ● Clear

EB111 CH110ST ● Clear Anti-fog

EB118 CH118S ● Sandstone Bronze

EB120 CH120S ● Gray

EB121 CH120ST ● Gray Anti-fog

Available in a Carhartt clamshell or polybag
Carhartt packaging design subject to change



Model No: EB120
Style No: CH120S



GENERAL SPECIFICATIONS

Weight: 26 gm
Lens base: 10 curve
Lens thickness: 2.3 mm
Overall length (lens - tip): 130 mm
Overall width (hinge - hinge): 137+1 mm
Closest point between temple tips:
105+5 mm
Closest point between lens: 11 mm

MATERIALS

Lens: polycarbonate (PC)
Temple: polycarbonate (PC)
Temple tips: thermoplastic rubbers (TPR)
Screw: stainless steel

LENS + TEMPLE MARKING SYMBOLS

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
S: Special purpose
c SEI Z94.3: CAN/CSA standard for eye and face protection devices

MODEL NO.	STYLE NO.	LENS MARKING	TEMPLE MARKING
EB110	CH110S	P+	P Z87 + / P c SEI Z94.3
EB111	CH110ST	P+	P Z87 + / P c SEI Z94.3
EB171	CH110STCS	P+	P Z87 + / P c SEI Z94.3
EB118	CH118S	P+S	P Z87 + / P c SEI Z94.3
EB120	CH120S	P+S	P Z87 + / P c SEI Z94.3
EB121	CH120ST	P+S	P Z87 + / P c SEI Z94.3
EB172	CH120STCS	P+S	P Z87 + / P c SEI Z94.3