

Cappture™ Plus ANSI • CE • CSA •



DIELECTRIC



INCLUDES STRAP

Dielectric // Fits over most prescription glasses
// Flexible rubber gasket // Temples extend from browbar to avoid interference with prescription frame's temples // Custom imprinting available

Rubber Gasket with Temples | 2 Variations

- S9910STMRG ● ● Clear **H2MAX AF**
- S9920STMRG ● ● Gray **H2MAX AF**



WATCH THE
CAPPTURE PLUS
VIDEO



Part No.	Lens Marking	Temple Marking
S9910STMRG	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
S9920STMRG	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's mark	P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices	Z87: ANSI standard for eye and face protection devices
+: High impact	+: High impact
X: Tested Anti-fog	c SEI Z94.3: CAN/CSA standard for eye and face protection devices
UV Filter Transmittance	
U6: .01% max effective far UV • .1% max near UV	
Visible Light Filters	
L2.5: 29% max visible light	

General Specifications	Materials
Weight: 51.7 gm	Lens: polycarbonate
Bridge: 23.1 mm	Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
Lens base: 2.5 curve	Nosepiece: polycarbonate
Lens size diagonal: 145.7 mm	Temple: polycarbonate
Lens size vertical: 51.5 mm	Hinge: nylon + polycarbonate
Lens thickness: 1.8 mm	
Overall length: 160 mm	
Overall width: 132.5 mm	