

Capstone 500 ANSI • CE • CSA • Ballistic •



Fits over most prescription glasses // Soft vinyl goggle body conforms to facial contours // Goggle provides protection against dust and chemical splash // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Some options passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Gray Body with Quick Release Strap | 4 Variations

- GG504T ●●●● Clear **H2X** AF
- GG504TM ●●●● Clear **H2MAX** AF
- GG504TIR3 ●● 3.0 IR Filter **H2X** AF
- GG504TIR5 ●● 5.0 IR Filter **H2X** AF

Chemical Green Body with Neoprene Strap | 1 Variation

- GC504TN ●● Clear **H2X** AF

i Fits over most prescription glasses.



GC504TN

Part No.	Lens Markings	Frame Markings	General Specifications	Materials
GG504T	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3	Weight: 92 gm	Lens: polycarbonate
GG504TM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3	PD: 68 mm	Body: polycarbonate & polyvinyl chloride
GG504TIR3	P Z87 + W5	P Z87 + D3 D4	Bridge: 45 mm	Headband: textile elastic
GG504TIR5	P Z87 + W3	P Z87 + D3 D4	Lens base: 5.5 curve	Nosepiece: polyvinyl chloride
GC504TN	P Z87 + U6	P Z87 + D3 D4	Lens size diagonal: 154 mm	
			Lens size vertical: 78 mm	
			Lens thickness: 2.3 mm	
			Strap length: 540 mm	

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 W: Welding filter
 X: Tested anti-fog
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test
 D4: Dust Test
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices