









Capstone 500 ANSI • CE • CSA • Ballistic •




Fits over most prescription glasses // Soft vinyl goggle body conforms to facial contours // Goggle provides protection against dust and chemical splash // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Some options passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Gray Body with Quick Release Strap | 4 Variations

-  GG 504T  Clear **H2X** AF
-  GG 504TM  Clear **H2MAX** AF
-  GG 504TIR3  3.0 IR Filter **H2X** AF
-  GG 504TIR5  5.0 IR Filter **H2X** AF

Chemical Green Body with Neoprene Strap | 1 Variation

-  GC 504TN  Clear **H2X** AF

 Fits over most prescription glasses.



GC 504TN

Part No.	Lens Markings	Frame Markings
GG504T	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3
GG504TM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3
GG504TIR3	P Z87 + W5	P Z87 + D3 D4
GG504TIR5	P Z87 + W3	P Z87 + D3 D4
GC504TN	P Z87 + U6	P Z87 + D3 D4

General Specifications

Weight: 92 gm
 PD: 68 mm
 Bridge: 45 mm
 Lens base: 5.5 curve
 Lens size diagonal: 154 mm
 Lens size vertical: 78 mm
 Lens thickness: 2.3 mm
 Strap length: 540 mm

Materials

Lens: polycarbonate
 Body: polycarbonate & polyvinyl chloride
 Headband: textile elastic
 Nosepiece: polyvinyl chloride

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 W: Welding filter
 X: Tested anti-fog
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test
 D4: Dust Test
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices