



## Ever-Lite® ANSI • CE • CSA •



Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available



### Black Frame | 19 Variations

- SB8610D ••• Clear
- SB8610DT ••• Clear **H2X AF**
- SB8610DTM ••• Clear **H2MAX AF**
- SB8620D ••• Gray
- SB8620DT ••• Gray **H2X AF**
- SB8620DTM ••• Gray **H2MAX AF**
- SB8623D •• Dark Gray
- SB8623DT •• Dark Gray **H2X AF**
- SB8624D ••• Photochromic
- SB8625DTM •• Light Gray **H2MAX AF**

- SB8630D ••• Amber
- SB8650SF • 5.0 IR Filter
- SB8660D •• Infinity Blue
- SB8660DT •• Infinity Blue **H2X AF**
- SB8660DTM ••• Infinity Blue **H2MAX AF**
- SB8660SF • 3.0 IR Filter
- SB8665D •• Ice Blue Mirror
- SB8680D ••• I/O Mirror
- SB8680DT ••• I/O Mirror AF

### Black and Lime Frame | 2 Variations

- SBL8610DTM •• Clear **H2MAX AF**
- SBL8620DTM •• Gray **H2MAX AF**



Photochromic lenses change from clear to dark after exposure to direct UV light. Lenses change from dark to clear after removal from UV light.

## Ever-Lite® Readers ANSI • CSA •



Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm // Custom imprinting available

### Black Frame | 14 Variations

- |   |  |
|---|--|
| SB8610R15 •• Clear +1.5 Mag                   | SB8620R15 •• Gray +1.5 Mag                   |
| SB8610R15TM •• Clear <b>H2MAX AF</b> +1.5 Mag | SB8620R15TM •• Gray <b>H2MAX AF</b> +1.5 Mag |
| SB8610R20 •• Clear +2.0 Mag                   | SB8620R20 •• Gray +2.0 Mag                   |
| SB8610R20TM •• Clear <b>H2MAX AF</b> +2.0 Mag | SB8620R20TM •• Gray <b>H2MAX AF</b> +2.0 Mag |
| SB8610R25 •• Clear +2.5 Mag                   | SB8620R25 •• Gray +2.5 Mag                   |
| SB8610R25TM •• Clear <b>H2MAX AF</b> +2.5 Mag | SB8620R25TM •• Gray <b>H2MAX AF</b> +2.5 Mag |
| SB8610R30 •• Clear +3.0 Mag                   |  |
| SB8610R30TM •• Clear <b>H2MAX AF</b> +3.0 Mag |  |



## Ever-Lite®

### General Specifications

Weight: 22 gm  
 PD: 64 mm  
 Bridge: 11.2 mm  
 Lens base: 8 curve  
 Lens size diagonal: 79.6 mm  
 Lens size vertical: 43.3 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 163.5 mm  
 Overall width (hinge - hinge): 134.3 mm  
 Closest point between temple tips: 70 mm  
 Closest point between lens: 11 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 + / P c SEI Z94.3
SB8610DT	P + U6	P Z87 + / P c SEI Z94.3
SB8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SB8620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SB8623D	P + S	P Z87 + / P c SEI Z94.3
SB8623DT	P + S	P Z87 + / P c SEI Z94.3
SB8624D	P + S	P Z87 + / P c SEI Z94.3
SB8625DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8630D	P + U6	P Z87 + / P c SEI Z94.3
SB8650SF	P+ W5	P Z87 +
SB8660D	P + S	P Z87 + / P c SEI Z94.3
SB8660DT	P + S	P Z87 + / P c SEI Z94.3
SB8660DTM	P + S X	P Z87 + / P c SEI Z94.3
SB8660SF	P+ W3	P Z87 +
SB8665D	P + S	P Z87 + / P c SEI Z94.3
SB8680D	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL8610DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SBL8620DTM	P + U6 L2.5 X	P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special Purpose  
 W: Welding filter  
 X: Tested Anti-fog

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

## Ever-Lite Readers

### General Specifications

Weight: 22 gm  
 PD: 64 mm  
 Bridge: 11.2 mm  
 Lens base: 8 curve  
 Lens size diagonal: 79.6 mm  
 Lens size vertical: 43.3 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 163.5 mm  
 Overall width (hinge - hinge): 134.3 mm  
 Closest point between temple tips: 70 mm  
 Closest point between lens: 11 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610R15	P + U6	+1.50 P Z87 + / P c SEI Z94.3
SB8610R15TM	P + U6 X	+1.50 P Z87 + / P c SEI Z94.3
SB8610R20	P + U6	+2.00 P Z87 + / P c SEI Z94.3
SB8610R20TM	P + U6 X	+2.00 P Z87 + / P c SEI Z94.3
SB8610R25	P + U6	+2.50 P Z87 + / P c SEI Z94.3
SB8610R25TM	P + U6 X	+2.50 P Z87 + / P c SEI Z94.3
SB8610R30	P + U6	+3.00 P Z87 + / P c SEI Z94.3
SB8610R30TM	P + U6 X	+3.00 P Z87 + / P c SEI Z94.3
SB8620R15	P + U6 L2.5	+1.50 P Z87 + / P c SEI Z94.3
SB8620R15TM	P + U6 L2.5 X	+1.50 P Z87 + / P c SEI Z94.3
SB8620R20	P + U6 L2.5	+2.00 P Z87 + / P c SEI Z94.3
SB8620R20TM	P + U6 L2.5 X	+2.00 P Z87 + / P c SEI Z94.3
SB8620R25	P + U6 L2.5	+2.50 P Z87 + / P c SEI Z94.3
SB8620R25TM	P + U6 L2.5 X	+2.50 P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special purpose  
 X: Tested Anti-fog

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L2.5: 29% max visible light

### Temple Marking Symbols

+1.50: magnification of +1.5  
 +2.00: magnification of +2.0  
 +2.50: magnification of +2.5  
 +3.00: magnification of +3.0

### P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

### + : High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices