



**Flex-Lyte™** ANSI • CE • CSA •



Soft nosepiece for snug fit // Special dielectric hinge design // Slim co-injected temples channel away sweat // Lightweight spectacle – 22 gm // Custom imprinting available

**Black and Gray Frame | 5 Variations**

- SBG10510D ●● Clear
- SBG10510DTM ●● Clear **H2MAX AF**
- SBG10520D ●● Gray
- SBG10520DTM ●● Gray **H2MAX AF**
- SBG10580D ●● I/O Mirror

**Black and Lime Frame | 5 Variations**

- SBL10510D ●●● Clear
- SBL10510DTM ●●● Clear **H2MAX AF**
- SBL10520D ●●● Gray
- SBL10520DTM ●●● Gray **H2MAX AF**
- SBL10580D ●●● I/O Mirror

Part No.	Lens Marking	Temple Marking
SBG10510D	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG10510DTM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBG10520D	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG10520DTM	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SBG10580D	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL10510D	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBL10510DTM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBL10520D	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBL10520DTM	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SBL10580D	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3

**General Specifications**

Weight: 21.9 gm  
 PD: 64 mm  
 Bridge: 14.6 mm  
 Lens base: 9 curve  
 Lens size diagonal: 82.3 mm  
 Lens size vertical: 45.3 mm  
 Lens thickness: 1.6 mm  
 Overall length (lens - tip): 160 mm  
 Overall width (hinge - hinge): 131.5 mm  
 Closest point between temple tips: 70 mm  
 Closest point between lens: 9.3 mm

**Materials**

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Nosepiece: thermoplastic rubbers (TPR)

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special Purpose  
 X: Tested Anti-fog  
 W: Welding filter  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV

**Visible Light Filters**  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

**Temple Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices