

POLYURETHANE DIPPED











GL403C

HPPE | Polyurethane





C€ CH CH CH

ANSI/ISEA 105 – CUT A2 | ABRASION 2 | PUNCTURE 3 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 2 | CUT TDM-100 B

Polyurethane coating on the palm and fingers for good grip and precision handling // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // Glove design offers excellent touch sensitivity and low particulate shed // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // Cutting Applications // Glass Handling // Metal Work

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



Packaging

GL403C 12 Pair 120 Pair		Outer Polybag	Case	Made in China
	GL403C	12 Pair	120 Pair	Made in China

Product markings may vary // Updated as of 08.23

Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	Laige 9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.