




POLYURETHANE DIPPED



GL404C

HPPE | Polyurethane

ANSI/ISEA 105



EN388



ANSI/ISEA 105 – CUT A4 | ABRASION 4 | PUNCTURE 4
 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 2 | CUT TDM-100 D

Polyurethane coating on the palm and fingers for good grip and precision handling // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // Glove design offers excellent touch sensitivity and low particulate shed // High-visibility coating for easy recognition // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // Construction // Manufacturing // Metal Fabrication

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Product markings may vary // Updated as of 06.23



Packaging

	Outer Polybag	Case	Made in China
GL404C	12 Pair	120 Pair	

Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.