

NITRILE DIPPED









.....

Nitrile

Abrasion

uncture

GL601

Nylon + Spandex | Nitrile | Micro-Foam





C€ CA

ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2 EN388 – ABRASION 4 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 15 gauge nylon/spandex liner is comfortable and breathable // Glove design offers distinctive touch sensitivity // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // General Assembly // General Duty // Handling Oily Parts // Horticulture // Warehousing

Glove Breakdown

Type: Dipped Glove				
Material: Micro-Foam Nitrile				
Outer Liner: 15 Gauge Nylon + Spandex Liner				
Cuff: Nylon + Latex Elastic				

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



Packaging

	Outer Polybag	Case	Made in China	
GL601	12 Pair	120 Pair	Made III CIIIIIa	

Product markings may vary // Updated as of 06.23

Glove Sizing

X-Small	Small	Medium	Large	X-Large	2X-Large	3X-Large
6	7	8	9	10	11	12

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.