

NITRILE DIPPED











GL602C3

HPPE | Nitrile | Micro-Foam







ANSI/ISEA 105 – CUT A2 | ABRASION 4 | PUNCTURE 3 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 2 | CUT TDM-100 B

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 13 gauge HPPE cutresistant liner delivers cool comfort for all-day wear // Knit cuff creates a snug fit to keep out debris // Packaging option for vending machines available

Suggested Applications

Automotive // Construction // Delivery // General Duty // Handling Oily Parts // Parts Assembly

Glove Breakdown

Type: Dipped Glove			
Material: Micro-Foam Nitrile			
Outer Liner: 13 Gauge HPPE			
Cuff: HPPE + Latex Elastic			

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Inner Polybag	Outer Polybag	Case
GL602C3	1 Pair	12 Pair	120 Pair
GL602C3VP	1 Pair Rolled	12 Pair	120 Pair
Made in China	a		

Product markings may vary // Updated as of 04.23



Glove Sizing

GL602C3 S - 2XL | GL602C3VP XS - 2XL

X-Small	Small	Medium	Large	X-Large	2X-Large
6	7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.