

NITRILE DIPPED











Puncture



GL607C

HPPE | Nitrile | Micro-Foam





C€ GK

ANSI/ISEA 105 – CUT A4 | ABRASION 5 | PUNCTURE 4 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 D

Micro-foam nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 13 gauge HPPE cutresistant liner delivers cool comfort for all-day wear // High-visibility liner for easy recognition // Knit cuff creates a snug fit to keep out debris // Hangtag option for retail display

Suggested Applications

Automotive // Construction // Manufacturing // Metal Fabrication

Glove Breakdown

Type: Dipped Glove
Material: Micro-Foam Nitrile
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

△ WARNING: Cancer and Reproductive Harm −P65Warnings.ca.gov
This product contains components that may be a potential risk to
allergic reactions (latex in the wrist cuff). Do not use in the event
of hypersensitivity signs or a known allergy to latex.

Packaging

	Outer Polybag	Case
GL607C	12 Pair	120 Pair
GL607CHT	12 Pair on Hangtags	120 Pair
Made in China		

Product markings may vary // Updated as of 04.23



Glove Sizing

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.



