




NITRILE DIPPED



GL608C

HPPE | Nitrile | Sandy



ANSI/ISEA 105 – CUT A6 | ABRASION 4 | PUNCTURE 4
 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 F

Sandy nitrile coating on the palm and fingers provides an effective grip in dry and oily situations // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // High-visibility liner for easy recognition // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // General Maintenance // Material Handling // Metal Fabrication

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov
 This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Outer Polybag	Case
GL608C	12 Pair	120 Pair
Made in China		

Product markings may vary // Updated as of 06.23



Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.