




NITRILE DIPPED



GL609C

HPPE | Nitrile | Sandy



ANSI/ISEA 105 – CUT A6 | ABRASION 6 | PUNCTURE 4
 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 E|IMPACT P

Sandy nitrile coating on the palm and fingers provides an effective grip in dry and oily situations // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // Custom-designed impact protection shields back of hand // Reinforced thumb reduces stress in high-wear area // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // Glass Handling // HVAC // Mining // Oil & Gas // Steel Handling // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic
TPR: Thermo Plastic Rubber

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov
 This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



Packaging

	Inner Polybag	Outer Polybag	Case	Made in China
GL609	1 Pair	6 Pair	60 Pair	

Product markings may vary // Updated as of 06.23

Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11	3X-Large 12
------------	-------------	------------	---------------	----------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.