

NITRILE DIPPED

Nitrile Abrasion

Puncture



GL614 Polyester | Nitrile | Smooth



ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2 EN388 – ABRASION 4 | CUT 1 | TEAR 2 | PUNCTURE 1 | CUT TDM-100 X

Smooth nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 10 gauge polyester liner offers a balance between comfort, durability, and moisture resistance // Knit cuff creates a snug fit to keep out debris

Suggested Applications

General Assembly // Inspection // Janitorial // Landscaping // Manufacturing // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Smooth Nitrile
Outer Liner: 13 Gauge Polyester
Cuff: Polyester + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

		Outer Polybag	Case
	GL614	12 Pair	120 Pair
	Made in China		

Product markings may vary // Updated as of 06.23



Glove Sizing

				0 14 1
Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.