

NITRILE DIPPED

Abrasion

Nitrile

Puncture



GL617

Nylon + Spandex | Nitrile | Micro-Foam



ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2 EN388 – ABRASION 4 | CUT 1 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

Micro-foam nitrile three-quarter dipped coating offers an excellent grip on dry or wet surfaces by channeling liquids away // 15 gauge nylon/spandex liner is comfortable and breathable // Glove design offers distinctive touch sensitivity // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // General Assembly // Genral Duty Purpose // Handling Oily Parts // Horticulture // Warehousing

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Micro-Foam
Outer Liner: 15 Gauge Nylon + Spandex
Cuff: Nylon + Latex Elastic

▲ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Packaging

	Outer Polybag	Case
GL617	12 Pair	120 Pair
Made in China		

Product markings may vary // Updated as of 06.23



Glove Sizing

SmallMediumLargeX-Large2X-Lar7891011

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.