



# INSULATED HPT DIPPED



HPT



Abrasion



Cut



Insulated



Puncture



Tear



Water-resistant

# GL902

Nylon | Acrylic | HPT

ANSI/ISEA 105



EN388



EN511



ANSI/ISEA 105 – CUT A2 | ABRASION 3 | PUNCTURE 2  
 EN388 – ABRASION 3 | CUT 2 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X  
 EN511 – CONTACT COLD 2

HPT coating on the palm and fingers repels water providing an effective grip in wet and oily environments while remaining soft in extremely low temperatures // 15 gauge nylon outer liner is strong yet lightweight // 7 gauge 360° inner acrylic liner delivers insulation and moisture resistance // Contact cold protection down to as low as -22°F/-30°C // Treated with Sanitized Actifresh® to control bacteria and odor // Knit cuff creates a snug fit to keep out debris

## Suggested Applications

Construction // Commercial Fishing // Food Processing // Outdoor Activities // Refrigerated Areas // Utilities

## Glove Breakdown

Type: Insulated Dipped Glove
Material: Hydropellent Technology (HPT)
Outer Liner: 15 Gauge Nylon
Inner Liner: 7 Gauge 360° Acrylic
Cuff: Nylon + Acrylic +Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Product markings may vary // Updated as of 08.23



## Packaging

	Outer Polybag	Case	Made in Pakistan
GL902	12 Pair	60 Pair	

## Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.