




## Integra® ANSI • CE • CSA •



Adjustable temples ensure reliable performance // Custom imprinting available

### Black Frame | 5 Variations

- SB410S ●●● Clear
- SB410ST ●●● Clear AF
- SB420S ●●● Gray
- SB450SF ●●● 5.0 IR Filter
- SB460SF ●●● 3.0 IR Filter



SM4



SN4



SNWR4



SR4

### Mixed Blue Frame | 1 Variation

- SM410S ●●● Clear

### Red, White & Blue Frame | 1 Variation

- SNWR410S ●●● Clear

### Black Ratchet Frame | 1 Variation

- SB410SR ●●● Clear

### Blue Frame | 1 Variation

- SN410S ●●● Clear

### Red Frame | 1 Variation

- SR410S ●●● Clear

Part No.	Lens Marking	Temple Marking
SB410S	P + U6	P Z87 + / P c SEI Z94.3
SB410ST	P + U6	P Z87 + / P c SEI Z94.3
SB420S	P + U6 L3	P Z87 + / P c SEI Z94.3
SB450SF	P + 5.0	P Z87 +
SB460SF	P + 3.0	P Z87 +
SB410SR	P + U6	P Z87 +
SM410S	P + U6	P Z87 + / P c SEI Z94.3
SN410S	P + U6	P Z87 + / P c SEI Z94.3
SNWR410S	P + U6	P Z87 + / P c SEI Z94.3
SR410S	P + U6	P Z87 + / P c SEI Z94.3

### General Specifications

Weight: 35 gm  
 PD: 68 mm  
 Lens base: 4 curve  
 Lens size diagonal: 138 mm  
 Lens size vertical: 39 mm  
 Lens thickness: 2.0 mm  
 Overall length (lens - tip): 85 mm  
 Overall width (hinge - hinge): 149 mm

### Materials

Lens: polycarbonate  
 Side shield: polycarbonate  
 Frame: nylon 66  
 Temples: nylon 66  
 Hinge: polycarbonate  
 Screw: nickel plated  
 Nosepiece: polycarbonate

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose  
 3.0: IR3 lens  
 5.0: IR5 lens

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L3: 18% Max. Visible Light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices