

Intrepid® II

ANSI • CE • Ballistic •



Nosepiece flange eliminates pressure on bridge of nose by evenly distributing weight of glass // Flexible rubber temples provide pressure-free fit behind the ear // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

Black Temples | 2 Variations

- SB8810S ● ● Clear
- SB8820S ● ● Gray



MARKINGS

| Part No. | Lens Marking | Temple Marking |
|----------|-----------------|----------------|
| SB8810S | P Z87 + U6 | P Z87 + |
| SB8820S | P Z87 + U6 L2.5 | P Z87 + |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

SPECIFICATIONS

General Specifications

Weight: 30 gm
 PD: 68 mm
 Bridge: 14.1 mm
 Lens base: 6.5 curve
 Lens size diagonal: 145.2 mm
 Lens size vertical: 50.6 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 172 mm
 Overall width (hinge - hinge): 136.4 mm
 Closest point between temple tips: 83 mm

Materials

Lens: polycarbonate
 Nose Piece: polycarbonate + thermoplastic elastomers
 Temples: polycarbonate + thermoplastic elastomers
 Hinge: polycarbonate
 Screw: stainless steel