



Intruder® ANSI • CE • CSA •



FOAM PADDING



READER OPTION

Integrated nosepiece // Lightweight frameless protection
// Foam padding is available in select options // Custom imprinting available

Lens and Temples | 10 Variations

- S4110S ●●● Clear
- S4110ST ●●● Clear AF
- S4110STM ●●● Clear **H2MAX** AF
- S4120S ●●● Gray
- S4120ST ●●● Gray AF
- S4120STM ●●● Gray **H2MAX** AF
- S4130S ●●● Amber
- S4160S ●● Infinity Blue
- S4170S ●● Silver Mirror
- S4180S ●● I/O Mirror



SB41



SN41



SR41

Black Temples | 1 Variation

- SB4110S ●● Clear

Blue Temples | 1 Variation

- SN4110S ●● Clear

Red Temples | 1 Variation

- SR4110S ●● Clear

Intruder Multi-Colors

ANSI • CE • CSA •

Sold in dozen quantity only // Comes with six assorted temple colors: red, blue, green, purple, orange and black // Multi-pack includes two of each temple color with clear lenses // Perfect for work areas where color coding is necessary // Custom imprinting available

Multi-Color Temples | 1 Variation

- S4110SMP ●●● Clear (Intruder)



Intruder®

General Specifications

Weight: 23.1 gm
 PD: 64 mm
 Bridge: 17.27 mm
 Lens base: 10 curve
 Lens size diagonal: 77.08 mm
 Lens size vertical: 43.38 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 156 mm
 Overall width (hinge - hinge): 135.5 mm
 Closest point between temples: 91.53 mm
 Closest point between lens: 16.67 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
S4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S4110ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
S4110STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
S4120S	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3
S4120ST	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3
S4120STM	P Z87 + U6 L3 X	P Z87 + / P c SEI Z94.3
S4130S	P Z87 + S	P Z87 + / P c SEI Z94.3
S4160S	P Z87 + S	P Z87 + / P c SEI Z94.3
S4170S	P Z87 + S	P Z87 + / P c SEI Z94.3
S4180S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SB4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SN4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SR4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S4110SMP	P Z87 + U6	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices