



FRAMELESS



H2MAX  
Anti-fog



IR  
Welding  
Filter

# LEGACY®

ANSI • CE/UKCA • CSA •

Lightweight spectacle works for any environment // Integrated side shields provide additional protection without interfering with peripheral vision // Brow guard shields eyes from dirt and debris // H2MAX and IR lens options // Custom imprinting available

## Lens and Temples | 8 Variations

- S10910S ●●● Clear
- S10910STM ●●● Clear **H2MAX AF**
- S10920S ●●● Gray
- S10920STM ●●● Gray **H2MAX AF**
- S10925S ●● Light Gray
- S10925STM ●● Light Gray **H2MAX AF**
- S10950SF ●●● 5.0 IR Filter
- S10960SF ●●● 3.0 IR Filter



## Materials

|                            |
|----------------------------|
| Lens: Polycarbonate        |
| Nosepiece: Polycarbonate   |
| Side Shield: Polycarbonate |
| Temples: Polycarbonate     |
| Screw: Stainless Steel     |



| Part No.  | Lens Marking      | Temple Marking          | Lens Marking Symbols                                   | Temple Marking Symbols  | Measurements                               |
|-----------|-------------------|-------------------------|--|---|--|
| S10910S   | P Z87 + U6        | P Z87 + / P c SEI Z94.3 | P: Manufacturer's mark                                 | P: Manufacturer's mark  | Weight: 23 gm                              |
| S10910STM | P Z87 + U6 X      | P Z87 + / P c SEI Z94.3 | Z87: ANSI standard for eye and face protection devices | Z87: ANSI standard for eye and face protection devices            | PD: 64 mm                                  |
| S10920S   | P Z87 + U6 L2.5   | P Z87 + / P c SEI Z94.3 | +: High impact   | +: High impact  | Bridge: 10.7 mm                            |
| S10920STM | P Z87 + U6 L2.5 X | P Z87 + / P c SEI Z94.3 | W: Welding filter                                      | c SEI Z94.3: CAN/CSA standard for eye and face protection devices | Lens base: 6 curve                         |
| S10925S   | P Z87 + U6 L1.7   | P Z87 + / P c SEI Z94.3 | X: Tested Anti-fog                                     |   | Lens size diagonal: 51.5 mm                |
| S10925STM | P Z87 + U6 L1.7 X | P Z87 + / P c SEI Z94.3 | <b>UV Filter Transmittance</b>                         |   | Lens size vertical: 46 mm                  |
| S10950SF  | P Z87 + W5        | P Z87 + / P c SEI Z94.3 | U6: .01% max effective far UV • .1% max near UV        |   | Lens thickness: 2 mm                       |
| S10960SF  | P Z87 + W6        | P Z87 + / P c SEI Z94.3 | <b>Visible Light Filters</b>                           |   | Overall length (lens - tip): 155 mm        |
|           |                   |                         | L1.7: 55% Max. Visible Light                           |   | Overall width (hinge - hinge): 136 mm      |
|           |                   |                         | L2.5: 29% max visible light                            |   | Closest point between temple tips: 98.3 mm |
|           |                   |                         |  |   | Closest point between lens: 20.3 mm        |