



Loadout™

Vented frame helps fight fogging while filtering dust and small particles

Foam padded for added protection and comfort

Integrated sleeve protects lens when not in use

Passes D3: Droplet and Splash Test – provides protection from droplets and splashes

Passes D4: Dust Test – provides protection from dust particles

Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Includes canvas storage case with MOLLE compatible snap straps

VGGB1510STM ●● [box]

Clear H2MAX Anti-fog Lens with Black Body



Loadout™ ballistic goggle shot with 12 gauge shotgun and 2 ¾ inch steel #6 at 25 yards

Meets ANSI Z87.1+ standards (●) and Ballistic MIL-PRF-32432 High Velocity Impact (●) standards. All lenses are hard coated polycarbonate scratch-resistant and provides 99% protection from harmful UV rays. For specific lens options visit our website or contact your sales representative.



Loadout™

General Specifications

Weight: 120.8 gm
 Lens base: 5.5 curve
 Lens thickness: 2.3 mm
 Bridge: 41.3 mm
 Lens size vertical: 79 mm
 Lens size diagonal: 163.2 mm
 Overall length: 73 mm
 Overall width: 195.5 mm

Materials

Lens: polycarbonate
 Body: thermoplastic elastomers (TPE)
 Foam: polyurethane
 Strap buckle: polycarbonate
 Headband: polyester

Part No.	Lens Marking	Frame Marking
VGGB1510STM	P Z87 + U6	P Z87 + D3 D4

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test
 D4: Dust Test

