



Ztek® ANSI • CE • CSA •



RUBBER TIPS

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit // Custom imprinting available

Lens and Temples | 18 Variations

	S2510S •••	Clear
	S2510ST •••	Clear H2X AF
	S2514S •••	1.5 IR Filter
	S2515S •••	Coffee
	S2520S •••	Gray
	S2520ST ••	Gray H2X AF
	S2530S •••	Amber
	S2540S •••	Orange
	S2550SF •	5.0 IR Filter
	S2560S •••	Infinity Blue
	S2560SF •	3.0 IR Filter
	S2560ST ••	Infinity Blue H2X AF
	S2565S ••	Purple Haze
	S2570S ••	Silver Mirror
	S2575S •••	Blue Mirror
	S2580S •••	I/O Mirror
	S2590S ••	Gold Mirror
	S25ARCS ••	Arc – 1.5 IR Filter



Mini Ztek ANSI • CE • CSA •

Mini Ztek has all the great features of Ztek in a design better suited for slimmer facial sizes



Mini Ztek is about 6% smaller than the Ztek.

S2514S is designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.

S25ARCS is great for use under the welding helmet – allowing welder to see work clearly without suffering “welder’s flash burn” from surrounding welders.

Lens and Temples | 8 Variations

	S2510SN •••	Clear
	S2510SNT ••	Clear H2X AF
	S2517SN ••	Pink
	S2520SN •••	Gray
	S2530SN •••	Amber
	S2560SN ••	Infinity Blue
	S2575SN •••	Blue Mirror
	S2580SN •••	I/O Mirror

Ztek® Readers ANSI • CE • CSA •











RUBBER TIPS



READER OPTION

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit // Custom imprinting available

Lens and Temples | 8 Variations

	S2510R15 •••	Clear	+1.5 Mag
	S2510R20 •••	Clear	+2.0 Mag
	S2510R25 •••	Clear	+2.5 Mag
	S2514R15 •	1.5 IR Filter	+1.5 Mag
	S2514R20 •	1.5 IR Filter	+2.0 Mag
	S2520R15 •	Gray	+1.5 Mag
	S2520R20 •	Gray	+2.0 Mag
	S2520R25 •	Gray	+2.5 Mag



S2514R is designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.

Ztek®

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 154 mm
 Overall width (hinge - hinge): 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Temple Marking
S2510S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S2510ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
S2514S	P Z87 + R1.5S	P Z87 + / P c SEI Z94.3
S2515S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2520S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
S2520ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
S2530S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S2540S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2550SF	P Z87 + W5	P Z87 +
S2560S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2560SF	P Z87 + W3	P Z87 +
S2560ST	P Z87 + S	P Z87 + / P c SEI Z94.3
S2565S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2570S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2575S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2580S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
S2590S	P Z87 + S	P Z87 + / P c SEI Z94.3
S25ARCS	P Z87 + R1.5S	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 W: Welding filter
 R: IR filter

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Mini Ztek

General Specifications

Weight: 20 gm
 PD: 50 mm
 Bridge: 12 mm
 Lens base: 10 curve
 Lens size diagonal: 73.8 mm
 Lens size vertical: 41 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 144 mm
 Overall width (hinge - hinge): 128 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Temple Marking
S2510SN	P Z87 H + U6	P Z87 H + / P c SEI Z94.3
S2510SNT	P Z87 H + U6	P Z87 H + / P c SEI Z94.3
S2517SN	P Z87 H + S	P Z87 H + / P c SEI Z94.3
S2520SN	P Z87 H + U6 L2.5	P Z87 H + / P c SEI Z94.3
S2530SN	P Z87 H + U6	P Z87 H + / P c SEI Z94.3
S2560SN	P Z87 H + S	P Z87 H + / P c SEI Z94.3
S2575SN	P Z87 H + S	P Z87 H + / P c SEI Z94.3
S2580SN	P Z87 H + U6 L1.7	P Z87 H + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 H: Small head size

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 H: Small head size
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Ztek® Readers

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length [lens - tip]: 154 mm
 Overall width [hinge - hinge]: 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Temple Marking	
S2510R15	P Z87 + U6	+1.50	P Z87 + / P c SEI Z94.3
S2510R20	P Z87 + U6	+2.00	P Z87 + / P c SEI Z94.3
S2510R25	P Z87 + R1.5S	+2.50	P Z87 + / P c SEI Z94.3
S2514R15	P Z87 + R1.5S	+1.50	P Z87 +
S2514R20	P Z87 + R1.5S	+2.00	P Z87 +
S2520R15	P Z87 + U6 L2.5	+1.50	P Z87 +
S2520R20	P Z87 + U6 L2.5	+2.00	P Z87 +
S2520R25	P Z87 + U6 L2.5	+2.50	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 R: IR filter
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L2.5: 29% max visible light

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices