

Overwatch® ANSI • Ballistic •



RUBBER TIPS

Soft nose-piece and rubber temple tips



Anti-fog scratch-resistant polycarbonate lens provides 99% UVA, UVB, and UVC protection

Passes Ballistic MIL-PRF-32432 High Velocity Impact standards


Packaged in a Venture Gear Tactical branded box with temple tag for counter top or pegboard display





Black Frame | 2 Variations

-  VGSB718T •• Bronze AF
-  VGSB722T •• Forest Gray AF

OD Green Frame | 2 Variations

-  VGSG718T •• Bronze AF
-  VGSG722T •• Forest Gray AF

Urban Gray Frame | 2 Variations

-  VGSUG710T •• Clear AF
-  VGSUG722T •• Forest Gray AF

General Specifications

Weight: 35.5 gm
 Bridge: 12.6 mm
 Lens base: 8 curve
 Lens size diagonal: 66.7 mm
 Lens size vertical: 42.3 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 160 mm
 Overall width (hinge - hinge): 131.5mm
 Closest point between lens: 15.1 mm
 Closest point between Temple Tips: 93 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: Nickel Silver
 Nose-piece: thermoplastic rubber (TPR)
 Frame: PCB

Part No.

VGSB718T
 VGSB722T
 VGSG718T
 VGSG722T
 VGSUG710T
 VGSUG722T

Lens Marking

P + S
 P + S
 P + S
 P + S
 P + S
 P + S

Frame Marking

P Z87 +
 P Z87 +
 P Z87 +
 P Z87 +
 P Z87 +
 P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High Impact
 S: Special Purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Packaging

Sold individually in a Venture Gear Tactical branded box
 Case: 60 pcs

All safety eyewear meets ANSI Z87.1+ standards (•) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant. Some options meet Canadian CSA Z94.3 (•) – SEI third-party certification or Ballistic MIL-PRF-32432 High Velocity Impact (•) standards. For specific lens options visit our website or contact your sales representative.