

**PMXSLIM®** ANSI • CE •



ADJUSTABLE  
NOSEPIECE



CO-INJECTED  
TEMPLES

Slim fit for smaller facial features // Soft adjustable nosepiece // Co-injected temple design includes soft rubber tips for a non-slip fit // Custom imprinting available

**Black Temples | 6 Variations**

- SB7110S •• Clear
- SB7110ST •• Clear **H2X AF**
- SB7120S •• Gray
- SB7120ST •• Gray **H2X AF**
- SB7138S •• Sandstone Bronze
- SB7180S •• I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB7110S	P Z87 + U6	P Z87 +	Weight: 25 gm	Lens: polycarbonate
SB7110ST	P Z87 + U6	P Z87 +	PD: 68 mm	Frame: polycarbonate
SB7120S	P Z87 + U6 L2.5	P Z87 +	Bridge: 14.5 mm	Temples: polycarbonate & thermoplastic elastomers
SB7120ST	P Z87 + U6 L2.5	P Z87 +	Lens base: 10 curve	Hinge: polycarbonate
SB7138S	P Z87 + S	P Z87 +	Lens size diagonal: 137.7 mm	Screw: stainless steel
SB7180S	P Z87 + U6 L1.7	P Z87 +	Lens size vertical: 45 mm	Side shields: polycarbonate
			Lens thickness: 2.3 mm	Nosepiece: polyvinyl chloride
			Overall length (lens - tip): 170 mm	
			Overall width (hinge - hinge): 129 mm	
			Closest point between temple tips: 86 mm	
			Closest point between lens: 9 mm	

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose

**UV Filter Transmittance**

U6: .01% max effective far UV • .1% max near UV

**Visible Light Filters**

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

**Temple Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact