


PMXTREME® ANSI • CE •



Built-in rubber nosepiece // Ventilated flexible temples with rubber temple tips // Includes black lanyard cord // Custom imprinting available

Black Frame with Cord | 11 Variations

- SB6310SP • Clear
- SB6310STP • Clear AF
- SB6320SP • Gray
- SB6320STP • Gray AF
- SB6330SP • Amber
- SB6345SP • Ice Orange Mirror
- SB6360SP • Infinity Blue
- SB6370SP • Silver Mirror
- SB6375SP • Blue Mirror
- SB6376SP • Smoke Green Mirror
- SB6380SP • I/O Mirror



SCM63



SR63



SS63

Camo Frame with Cord | 3 Variations

- SCM6310STP • Clear AF
- SCM6318STP • Sandstone Bronze AF
- SCM6320STP • Gray AF

Red Frame with Cord | 1 Variation

- SR6320SP • Gray

Silver Frame with Cord | 2 Variations

- SS6310SP • Clear
- SS6365SP • Ice Blue Mirror

PMXTREME LED ANSI • CE •



Super bright swiveling LED bulbs (three lumens per side) allow you to see in dark places while keeping your hands free // Built-in rubber nosepiece and rubber temple tips // The alkaline batteries provide up to 50 hours of use before replacing. Three L1154F (LR44) alkaline batteries per temple (six total) are included // Easy to use push button on/off switches are located at the top of each temple // Custom imprinting available

Black Frame | 2 Variations

- SB6310SPLED • Clear
- SB6310STPLED • Clear AF



i Replacement batteries are not available.

PMXTREME Rx ANSI •




Includes Rx insert which accommodates -3.0 to +3.0 prescription lenses // Take insert to local optometrist for Rx lens installation // Custom imprinting available



Black Frame | 2 Variations

- SB6310STRX • Clear AF
- SB6320STRX • Gray AF

PMXTREME® Readers ANSI •



Built-in rubber nosepiece // Ventilated flexible temples with rubber temple tips // Includes black lanyard cord // Custom imprinting available



Black Frame with Cord | 3 Variations

- SB6310SPR15 • Clear +1.5 Mag
- SB6310SPR20 • Clear +2.0 Mag
- SB6310SPR25 • Clear +2.5 Mag

PMXTREME LED Readers ANSI •



Super bright swiveling LED bulbs (three lumens per side) allow you to see in dark places while keeping your hands free // Built-in rubber nosepiece and rubber temple tips // The alkaline batteries provide up to 50 hours of use before replacing. Three L1154F (LR44) alkaline batteries per temple (six total) are included // Easy to use push button on/off switches are located at the top of each temple

Black Frame | 3 Variations

- SB6310STPLEDR15 • Clear AF +1.5 Mag
- SB6310STPLEDR20 • Clear AF +2.0 Mag
- SB6310STPLEDR25 • Clear AF +2.5 Mag

i Replacement batteries are not available.



PMXTREME®

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310SP	P + U6	P Z87 +
SB6310STP	P + U6	P Z87 +
SB6320SP	P + U6 L3	P Z87 +
SB6320STP	P + U6 L3	P Z87 +
SB6330SP	P + U6	P Z87 +
SB6345SP	P + L3	P Z87 +
SB6360SP	P + U6 L1.3	P Z87 +
SB6370SP	P + L3	P Z87 +
SB6375SP	P + L3	P Z87 +
SB6376SP	P + L3	P Z87 +
SB6380SP	P + U6 L1.7	P Z87 +
SCM6310STP	P + U6	P Z87 +
SCM6318STP	P + U6 L2.5	P Z87 +
SCM6320STP	P + U6 L3	P Z87 +
SR6320SP	P + U6 L3	P Z87 +
SS6310SP	P + U6	P Z87 +
SS6365SP	P + L3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

PMXTREME LED

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310SPLED	P + U6	P Z87 +
SB6310STPLED	P + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

PMXTREME Rx

General Specifications

Weight: 29 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 146 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Rx Insert: thermoplastic

Part No.	Lens Marking	Temple Marking
SB6310STRX	P + U6	P Z87 +
SB6320STRX	P + U6 L3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

PMXTREME® Readers

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310SPR15	P + U6	+1.50 P Z87 +
SB6310SPR20	P + U6	+2.00 P Z87 +
SB6310SPR25	P + U6	+2.50 P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

PMXTREME® LED Readers

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Temple tips: rubber
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber

Part No.	Lens Marking	Temple Marking
SB6310STPLEDR15	P + U6	+1.50 P Z87 +
SB6310STPLEDR20	P + U6	+2.00 P Z87 +
SB6310STPLEDR25	P + U6	+2.50 P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact