



RPD3001 Series Metal Detectable Reusable Corded Earplugs

NRR 25dB // SNR 30dB

Three flexible rubber flanges form a secure seal
Embedded with metal shavings in plug and cord

PART NO.

RPD3001 • •

STANDARDS

Meets ANSI S3.19-1974 and
CE EN-352:2002

GENERAL SPECIFICATIONS

Reusable: Yes

Metal Detectable: Yes

Plug Material: TP Rubber

Plug Color: Blue

Plug Dimension: 2.6 x 1.2 cm

Cord Material: PVC with embedded metal shavings

Cord Color: Blue

Cord Length: 75cm

SIZE

One size fits most

PACKAGING

RPD3001 - Sold Individually | 100 per box | 10 boxes per case

RPD3001



PRODUCT GUIDELINES

The level of noise entering a person's ear, when hearing protection is worn as directed is approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).

2. The NRR is 32 decibels (dB).

3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in continuous noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.