

Solo[®] ANSI • CE • CSA •

Temples are vented to reduce fogging // Custom imprinting available

Lens and Temples | 4 Variations

- S510S ••• Clear
- S510SD •• Clear Dispenser pack – 12 per box
- S510SJ • Clear Jumbo
- S520S • Gray

i Only S510SJ is designed to be used over prescription spectacles.



General Specifications

Weight: 46 gm | 53 gm (Jumbo)
 Lens base: 4 curve | 2.5 curve (Jumbo)
 Lens size diagonal: 145 mm
 Lens size vertical: 45 mm | 50 mm (Jumbo)
 Lens thickness: 2 mm
 Overall length (lens - tip): 108 mm
 Overall width (hinge - hinge): 159 mm | 165 mm (Jumbo)

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate
 Side Shield: polycarbonate
 Hinge: polycarbonate
 Nosepiece: polycarbonate

Part No.

S510S
 S510SD
 S510SJ
 S520S

Lens Marking

P Z87+U6
 P Z87+U6
 P Z87+U6
 P Z87+U6 L3

Temple Marking

P Z87+ / P c SEI Z94.3
 P Z87+ / P c SEI Z94.3
 P Z87+
 P Z87+

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L3: 18% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices