

Half Frame Slim Fit Safety Glasses

Spokane®

ANSI CSA



Rubber Nosepiece



Polarized



Ultraviolet Protection



Scratch Resistant

FEATURES

Rubber nosepiece

Straight-back co-injected temples

MODEL NO. STYLE NO.

ES371 CHB310DCC ● Clear

ES378 CHB318DCC ● Sandstone Bronze

ES372 CHB320DCC ● Gray

MODEL NO. STYLE NO.

ES310 CHB310D ● Clear

ES318 CHB318D ● Sandstone Bronze

ES319 CHB319 ● Polarized Sandstone Bronze

ES320 CHB320D ● Gray

ES321 CHB321 ● Polarized Gray

ES361 CHB361 ● Polarized Blue Mirror

Available in a Carhartt capture clam or polybag
Carhartt packaging design subject to change



Model No: ES361
Style No: CHB361



GENERAL SPECIFICATIONS

Weight: 24 gm
 Bridge: 15 mm
 Lens base: 8 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 42 mm
 Lens thickness: 2.0 mm
 Overall length (lens - tip): 125 mm
 Overall width (hinge - hinge): 137+1 mm
 Closest point between temple tips: 107+5 mm
 Closest point between lens: 17 mm

MATERIALS

Lens: polycarbonate (PC)
 Frame: polycarbonate (PC)
 Temple tips: thermoplastic rubbers (TPR)
 Screw: stainless steel
 Nose pad: thermoplastic rubbers (TPR)

LENS + FRAME MARKING SYMBOLS

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

MODEL NO.	STYLE NO.	LENS MARKING	FRAME MARKING
ES371	CHB310DCC	P	P Z87+ / P c SEI Z94.3
ES310	CHB310D	P	P Z87+ / P c SEI Z94.3
ES378	CHB318DCC	P+S	P Z87+ / P c SEI Z94.3
ES318	CHB318D	P+S	P Z87+ / P c SEI Z94.3
ES319	CHB319	P+S	P Z87+ / P c SEI Z94.3
ES372	CHB320DCC	P+S	P Z87+ / P c SEI Z94.3
ES320	CHB320D	P+S	P Z87+ / P c SEI Z94.3
ES321	CHB321	P+S	P Z87+ / P c SEI Z94.3
ES361	CHB361	P+S	P Z87+ / P c SEI Z94.3