


Surveyor[®] ANSI •



Rubber comfort-fit temples // Soft nosepiece // Custom imprinting available

Black Temples | 4 Variations

- SB6110ST • Clear AF
- SB6120S • Gray
- SB6145S • Ice Orange Mirror
- SB6170S • Silver Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB6110ST	P + U6	P Z87 +	Weight: 24 gm	Lens: polycarbonate
SB6120S	P + U6 L3	P Z87 +	Bridge: 24.8 mm	Frame: polycarbonate
SB6145S	P + L3	P Z87 +	Lens base: 8 curve	Temples: polycarbonate
SB6170S	P + L3	P Z87 +	Lens size diagonal: 67 mm	Temple tips: thermoplastic rubbers (TPR)
			Lens size vertical: 41 mm	Nosepiece: thermoplastic rubbers (TPR)
			Lens thickness: 2.1 mm	Hinge screw: silver nickel
			Overall length (lens - tip): 116 mm	
			Overall width (hinge - hinge): 142mm	

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's mark	P: Manufacturer's mark
+: High impact	Z87: ANSI standard for eye and face protection devices
UV Filter Transmittance	+: High impact
U6: .01% max effective far UV • .1% max near UV	
Visible Light Filters	
L3: 18% Max. Visible Light	