



Waverton

Flexible rubber nosepiece
Co-injected straight-back temples



VGSB1110DB • (polybag)
Clear Lens with Black Frame



VGSB1126DB • (polybag)
Forest Gray Lens with Black Frame



VGSB1170DB • (polybag)
Silver Mirror Lens with Black Frame



VGSB1165DB • (polybag)
Ice Blue Mirror Lens with Black Frame



VGSBR1118DB • (polybag)
Bronze Lens with Brown Frame



VGSBR1156DB • (polybag)
Multi-color Mirror Lens with Brown Frame

General Specifications

Weight: 24.4 gm
Lens base: 8 curve
Lens thickness: 2 mm
Bridge: 17mm
Lens size vertical: 41 mm
Lens size diagonal: 72 mm
Overall length (lens - tip): 131 mm
Overall width (hinge - hinge): 129+/-1mm
Closest point between temple tips: 95mm+/-5mm
Closest point between lens: 11 mm

Materials

Lens: polycarbonate
Frame: polycarbonate
Screw: stainless steel

Part No.

VGSB1110DB
VGSB1126DB
VGSB1170DB
VGSB1165DB
VGSBR1118DB
VGSBR1156DB

Lens Marking

P + S
P + S
P + S
P + S
P + S
P + S

Temple Marking

P Z87 +
P Z87 +
P Z87 +
P Z87 +
P Z87 +
P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
S: Special purpose
+: High impact

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact

All safety eyewear meets ANSI Z87.1+ (•) standards. All lenses are hard coated polycarbonate scratch-resistant and provide 99% protection from harmful UV rays.