

XS3 PLUS® ANSI • CSA •



Unique slim temple design with co-injected temple tips //
 Flame resistant foam padding // Detachable strap // Passes
 D3: Droplet and Splash Test // Custom imprinting available

Black Frame | 3 Variations

- SB4610STP •• Clear H2X AF
- SB4620STP •• Gray H2X AF
- SB4680STP •• I/O Mirror AF



General Specifications

Weight: 34 gm
 PD: 68 mm
 Bridge: 19.3 mm
 Lens base: 7 curve
 Lens size diagonal: 131 mm
 Lens size vertical: 50 mm
 Lens thickness: 2.1 mm
 Closest point between temple tips: 79 mm
 Overall length (lens-tip): 155 mm
 Overall width (hinge-hinge): 145 mm

Materials

Lens: polycarbonate
 Frame: nylon 66
 Strap: polyester
 Nosepiece: polycarbonate
 Temple: polycarbonate
 Temple tips: thermoplastic elastomers
 Sponge: chloroprene rubber
 Hinge: polycarbonate
 Screw: stainless steel

Part No.

SB4610STP
 SB4620STP
 SB4680STP

Lens Markings

P Z87 + U6 D3
 P Z87 + U6 L2.5 D3
 P Z87 + U6 L1.7 D3

Frame Markings

P Z87 + D3 / P c SEI Z94.3
 P Z87 + D3 / P c SEI Z94.3
 P Z87 + D3 / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices