










XSG® ANSI • CE • CSA • Ballistic •



Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards
Custom imprinting available

Black Frame | 4 Variations

-  GB4010ST  Clear **H2X AF**
-  GB4010STM  Clear **H2MAX AF**
-  GB4020ST  Gray **H2X AF**
-  GB4080ST  I/O Mirror AF







XSG Kit ANSI • CE • Ballistic •



Interchangeable lenses, temples, and strap // Black nylon case for storage // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

Black Frame | 3 Interchangeable Options

-    GB4010KIT 
- Clear **H2X AF** Gray **H2X AF** Amber **H2X AF**









XSG® Readers ANSI • CSA •



Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included // Custom imprinting available

Black Frame | 3 Variations

-  GB4010STR15  Clear **H2X AF** +1.5 Mag
-  GB4010STR20  Clear **H2X AF** +2.0 Mag
-  GB4010STR25  Clear **H2X AF** +2.5 Mag



XSG® and XSG Kit

General Specifications

Weight: 28 gm
 PD: 68 mm
 Bridge: 13.7 mm
 Lens base: 8 curve
 Lens size diagonal: 66.3 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 163 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temple tips: 56 mm
 Closest point between lens: 18.5 mm
 Strap length: 420 mm

Materials

Lens: polycarbonate
 Foam: polycarbonate & ethylene vinyl acetate
 Frame: nylon
 Temples: polycarbonate & polyvinyl chloride
 Strap: polyester
 Screw: stainless steel
 Nosepiece: ethylene vinyl acetate

Part No.	Lens Marking	Temple Marking
GB4010ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
GB4010STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
GB4020ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
GB4080ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
GB4010KIT	P Z87 + U6	P Z87 + / P c SEI Z94.3
	P Z87 + U6 L2.5	
	P Z87 + U6	

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

XSG® Readers

General Specifications

Weight: 35 gm
 PD: 68 mm
 Bridge: 13.7 mm
 Lens base: 8 curve
 Lens size diagonal: 66.3 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 163 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temple tips: 56 mm
 Closest point between lens: 18.5 mm
 Strap length: 420 mm

Materials

Lens: polycarbonate
 Foam: polycarbonate & ethylene vinyl acetate
 Frame: nylon
 Temples: polycarbonate & polyvinyl chloride
 Strap: polyester
 Screw: stainless steel
 Nosepiece: ethylene vinyl acetate

Part No.	Lens Markings	Temple Markings
GB4010STR15	P Z87 + U6	+1.50 P Z87 + / P c SEI Z94.3
GB4010STR20	P Z87 +	+2.00 P Z87 + / P c SEI Z94.3
GB4010STR25	P Z87 +	+2.50 P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices