










## XSG® ANSI • CE • CSA • Ballistic •



Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards  
Custom imprinting available

### Black Frame | 4 Variations

-  GB4010ST  Clear **H2X AF**
-  GB4010STM  Clear **H2MAX AF**
-  GB4020ST  Gray **H2X AF**
-  GB4080ST  I/O Mirror AF







## XSG Kit ANSI • CE • Ballistic •



Interchangeable lenses, temples, and strap // Black nylon case for storage // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

### Black Frame | 3 Interchangeable Options

-    GB4010KIT 
- Clear **H2X AF** Gray **H2X AF** Amber **H2X AF**









## XSG® Readers ANSI • CSA •



Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included // Custom imprinting available

### Black Frame | 3 Variations

-  GB4010STR15  Clear **H2X AF** +1.5 Mag
-  GB4010STR20  Clear **H2X AF** +2.0 Mag
-  GB4010STR25  Clear **H2X AF** +2.5 Mag



## XSG® and XSG Kit

### General Specifications

Weight: 28 gm  
 PD: 68 mm  
 Bridge: 13.7 mm  
 Lens base: 8 curve  
 Lens size diagonal: 66.3 mm  
 Lens size vertical: 44 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 163 mm  
 Overall width (hinge - hinge): 136.5 mm  
 Closest point between temple tips: 56 mm  
 Closest point between lens: 18.5 mm  
 Strap length: 420 mm

### Materials

Lens: polycarbonate  
 Foam: polycarbonate & ethylene vinyl acetate  
 Frame: nylon  
 Temples: polycarbonate & polyvinyl chloride  
 Strap: polyester  
 Screw: stainless steel  
 Nosepiece: ethylene vinyl acetate

Part No.	Lens Marking	Temple Marking
GB4010ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
GB4010STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
GB4020ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
GB4080ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
GB4010KIT	P Z87 + U6	P Z87 + / P c SEI Z94.3
	P Z87 + U6 L2.5	
	P Z87 + U6	

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 X: Tested Anti-fog

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

## XSG® Readers

### General Specifications

Weight: 35 gm  
 PD: 68 mm  
 Bridge: 13.7 mm  
 Lens base: 8 curve  
 Lens size diagonal: 66.3 mm  
 Lens size vertical: 44 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 163 mm  
 Overall width (hinge - hinge): 136.5 mm  
 Closest point between temple tips: 56 mm  
 Closest point between lens: 18.5 mm  
 Strap length: 420 mm

### Materials

Lens: polycarbonate  
 Foam: polycarbonate & ethylene vinyl acetate  
 Frame: nylon  
 Temples: polycarbonate & polyvinyl chloride  
 Strap: polyester  
 Screw: stainless steel  
 Nosepiece: ethylene vinyl acetate

Part No.	Lens Markings	Temple Markings
GB4010STR15	P Z87 + U6	+1.50 P Z87 + / P c SEI Z94.3
GB4010STR20	P Z87 +	+2.00 P Z87 + / P c SEI Z94.3
GB4010STR25	P Z87 +	+2.50 P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Temple Marking Symbols

+1.50: magnification of +1.5  
 +2.00: magnification of +2.0  
 +2.50: magnification of +2.5  
 P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices