







Ztek® ANSI • CE • CSA •



RUBBER TIPS

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit // Custom imprinting available

Lens and Temples | 18 Variations

| | | |
|---|-------------|-----------------------------|
|  | S2510S ••• | Clear |
|  | S2510ST ••• | Clear H2X AF |
|  | S2514S ••• | 1.5 IR Filter |
|  | S2515S ••• | Coffee |
|  | S2520S ••• | Gray |
|  | S2520ST ••• | Gray H2X AF |
|  | S2530S ••• | Amber |
|  | S2540S ••• | Orange |
|  | S2550SF ••• | 5.0 IR Filter |
|  | S2560S ••• | Infinity Blue |
|  | S2560SF ••• | 3.0 IR Filter |
|  | S2560ST ••• | Infinity Blue H2X AF |
|  | S2565S ••• | Purple Haze |
|  | S2570S ••• | Silver Mirror |
|  | S2575S ••• | Blue Mirror |
|  | S2580S ••• | I/O Mirror |
|  | S2590S ••• | Gold Mirror |
|  | S25ARCS ••• | Arc – 1.5 IR Filter |



Mini Ztek ANSI • CE • CSA •

Mini Ztek has all the great features of Ztek in a design better suited for slimmer facial sizes



Mini Ztek is about 6% smaller than the Ztek.

S2514S is designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.

S25ARCS is great for use under the welding helmet – allowing welder to see work clearly without suffering “welder’s flash burn” from surrounding welders.

Lens and Temples | 8 Variations

| | | |
|---|--------------|---------------------|
|  | S2510SN ••• | Clear |
|  | S2510SNT ••• | Clear H2X AF |
|  | S2517SN ••• | Pink |
|  | S2520SN ••• | Gray |
|  | S2530SN ••• | Amber |
|  | S2560SN ••• | Infinity Blue |
|  | S2575SN ••• | Blue Mirror |
|  | S2580SN ••• | I/O Mirror |

Ztek® Readers ANSI • CE • CSA •











RUBBER TIPS



READER OPTION

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit // Custom imprinting available

Lens and Temples | 8 Variations

| | | | |
|---|--------------|---------------|----------|
|  | S2510R15 ••• | Clear | +1.5 Mag |
|  | S2510R20 ••• | Clear | +2.0 Mag |
|  | S2510R25 ••• | Clear | +2.5 Mag |
|  | S2514R15 ••• | 1.5 IR Filter | +1.5 Mag |
|  | S2514R20 ••• | 1.5 IR Filter | +2.0 Mag |
|  | S2520R15 ••• | Gray | +1.5 Mag |
|  | S2520R20 ••• | Gray | +2.0 Mag |
|  | S2520R25 ••• | Gray | +2.5 Mag |



S2514R is designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.

Ztek®

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 154 mm
 Overall width (hinge - hinge): 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

| Part No. | Lens Marking | Temple Marking |
|----------|-----------------|-------------------------|
| S2510S | P Z87 + U6 | P Z87 + / P c SEI Z94.3 |
| S2510ST | P Z87 + U6 | P Z87 + / P c SEI Z94.3 |
| S2514S | P Z87 + R1.5S | P Z87 + / P c SEI Z94.3 |
| S2515S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2520S | P Z87 + U6 L2.5 | P Z87 + / P c SEI Z94.3 |
| S2520ST | P Z87 + U6 L2.5 | P Z87 + / P c SEI Z94.3 |
| S2530S | P Z87 + U6 | P Z87 + / P c SEI Z94.3 |
| S2540S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2550SF | P Z87 + W5 | P Z87 + |
| S2560S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2560SF | P Z87 + W3 | P Z87 + |
| S2560ST | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2565S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2570S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2575S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S2580S | P Z87 + U6 L1.7 | P Z87 + / P c SEI Z94.3 |
| S2590S | P Z87 + S | P Z87 + / P c SEI Z94.3 |
| S25ARCS | P Z87 + R1.5S | P Z87 + / P c SEI Z94.3 |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 W: Welding filter
 R: IR filter

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Mini Ztek

General Specifications

Weight: 20 gm
 PD: 50 mm
 Bridge: 12 mm
 Lens base: 10 curve
 Lens size diagonal: 73.8 mm
 Lens size vertical: 41 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 144 mm
 Overall width (hinge - hinge): 128 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

| Part No. | Lens Marking | Temple Marking |
|----------|-------------------|---------------------------|
| S2510SN | P Z87 H + U6 | P Z87 H + / P c SEI Z94.3 |
| S2510SNT | P Z87 H + U6 | P Z87 H + / P c SEI Z94.3 |
| S2517SN | P Z87 H + S | P Z87 H + / P c SEI Z94.3 |
| S2520SN | P Z87 H + U6 L2.5 | P Z87 H + / P c SEI Z94.3 |
| S2530SN | P Z87 H + U6 | P Z87 H + / P c SEI Z94.3 |
| S2560SN | P Z87 H + S | P Z87 H + / P c SEI Z94.3 |
| S2575SN | P Z87 H + S | P Z87 H + / P c SEI Z94.3 |
| S2580SN | P Z87 H + U6 L1.7 | P Z87 H + / P c SEI Z94.3 |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 H: Small head size

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 H: Small head size
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Ztek® Readers

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length [lens - tip]: 154 mm
 Overall width [hinge - hinge]: 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

| Part No. | Lens Marking | Temple Marking | |
|----------|-----------------|----------------|-------------------------|
| S2510R15 | P Z87 + U6 | +1.50 | P Z87 + / P c SEI Z94.3 |
| S2510R20 | P Z87 + U6 | +2.00 | P Z87 + / P c SEI Z94.3 |
| S2510R25 | P Z87 + R1.5S | +2.50 | P Z87 + / P c SEI Z94.3 |
| S2514R15 | P Z87 + R1.5S | +1.50 | P Z87 + |
| S2514R20 | P Z87 + R1.5S | +2.00 | P Z87 + |
| S2520R15 | P Z87 + U6 L2.5 | +1.50 | P Z87 + |
| S2520R20 | P Z87 + U6 L2.5 | +2.00 | P Z87 + |
| S2520R25 | P Z87 + U6 L2.5 | +2.50 | P Z87 + |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 R: IR filter
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L2.5: 29% max visible light

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices