

TIME



2005




8007



1010



1020



8006



8004



8048



7011



7036



7019



3090



3094



7008



7023



7026



3012



6070



3082



4066



6034




6031



4079




4021



6026



6091



6001



4022



6018

# Specification

SPECIFICATION	STANDARD	TOLERANCE	ACHEIVED
COMPOSITION	100% RECYCLED POLYESTER		
ENVIRONMENTAL	OEKO-TEX Standard 100	RECYCLED P.E.T BOTTLES	
ABRASION	ISO 12947-2 (Martindale)	± 10%	-
WIDTH (cm)	-	± 2%	140
WEIGHT (g/lm)	EN 12127	± 5%	350
PILLING (2000 rubs)	ISO 12945-2	from 4 to 5	5
LIGHT FASTNESS (blue scale)	ISO 105-B02 (Xoenotest)	from 5 to 8	6
FASTNESS TO RUBBING	ISO 105-X12 (Crockmeter)	from 4 to 5	4/5 (grey scale)

Slight colour variation within commercial tolerance may occur between batches due to properties of textiles


Digital fabric image may not be colour accurate. Always request fabric sample before ordering

## FLAMMABILITY

EN 1021-1&2 Cigarette & Match  
 BS 7176 Medium Hazard  
 BS 5852 Ignition source/ Crib 5  
 UNI 9175 Class 1 IM  
 California TB117

Flammability performance is dependent upon the foam used

## CLEANING AND WASHING



# inloom

fabrics