

SPECIFICATIONS

Specification		BB-800	BB-900	BB-1000
Power Rating		Australia or Europe: 220 – 240V~, 50/60Hz , 600 – 700W America or Canada: 120Vac, 60Hz, 660W		
Water inlet type	Type	Direct Inlet flow type		
	Water inlet pressure	0.4 ~ 7.5 kgf/cm ² (5.69 psi ~ 106.7psi)		
Power cord		(1.2m (4 feet): AMERICA) / (1.8m:Australia or Europe)		
Wash Device	Posterior Wash	Max. 1.2 l /min (Max. 0.32 GPM)		
	Feminine Wash	Max. 1.2 l /min (Max. 0.32 GPM)		
	Water Pressure Adjustable	5 Levels		
	Warm Water Temperature	Room Temp – 40°C (Room Temp. 104°F)		
	Heater	600 W		
	Safety Devices	Thermal fuse, Thermal switch, Float switch		
Heated Seat	Temperature	Room Temp ~ 41°C (Room Temp. ~ 105.8°F)		
	Heater	55 W		
	Safety Device	Thermal fuse		
Warm Air Dryer Device	Adjustable Dry Temperature (Room Temp~45°C)			
	Heater (250W)	○	○	○
	Safety Device (Thermal fuse, bimetal)			
Turbo& Enema Function		○	○	○
Deodorizer		-	○	○
Remote control		-	-	○
Inlet water temperature		3°C~ 35°C (37.4°F ~ 95°F)		
Ambient Temperature		3°C~ 40°C (37.4°F ~ 104°F)		
Dimension	Elongated(Control)	W : 495mm (19.4 inch) L : 525mm (20.6 inch) H : 185mm (7.28 inch)	Round (Control) W : 495mm (19.4 inch) L : 493mm (19.4 inch) H : 185mm (7.28 inch)	Elongated (Remote) W : 475mm (18.7 inch) L : 525mm (20.6 inch) H : 185mm (7.28 inch)
	Round (Remote)	W : 475mm (18.7 inch) L : 493mm (19.4 inch) H : 185mm (7.28 inch)		
Weight (kg)		5.3kg	5.4kg	5.2kg