

BA210 Series

BA210 LED BINOCULAR





BA210 Series

BA210 LED BINOCULAR

| | |
|----------------------------------|---|
| Optical system | Colour Corrected Infinity Optical System (CCIS®) |
| Observation tube | Binocular head, Siedentopf type |
| Inclination | 30° inclined, 360° rotating |
| Interpupillary distance | 55-75mm |
| Diopter adjustment | On both eyepieces, +/- 5 diopter |
| Eyepieces | Widefield N-WF10X/20mm with diopter adjustment |
| Nosepiece | Reversed quadruple |
| Objective classification | CCIS® EC Plan Achromatic, DIN |
| Objectives | 4X/0.10 (WD 15.9mm), 10X/0.25 (WD 17.4mm), 40X/0.65/S (WD 0.5mm), 100X/1.25/S-Oil (WD 0.15mm) |
| Objective mounting thread | W 4/5"x1/36" (RMS standard) |
| Stand type | Upright |
| Stage | Mechanical stage with built-in low position coaxial stage control and sample holder |
| Stage size | 140x135mm |
| Travel range X&Y | 76x50mm |
| Condenser | Focusable Abbe condenser N.A. 1.25 with slot for contrast sliders |
| Diaphragm | Iris diaphragm |
| Focus mechanism | Coaxial coarse and fine focusing system with tension adjustment |
| Fine focus precision | 2µm |
| Focusing stroke | 25mm |
| Upper limit stop | Upper limit stop preset but adjustable |
| Filter holder | On top of the illuminator |
| Transmitted illumination | LED 3W with intensity control |
| Transformer | Internal |
| Power supply | 100-240V (CE) |
| Accessories included | Dust cover, power cord, Allen key, Immersion oil (5ml), spare fuse, cord hanger, thumb screw |
| Dimensions LxWxH | 360x220x395mm |
| Net weight | 7.2kg |