



Metal guard system supplied as part of a comprehensive kit package



The MAX40V offers a 145mm stroke and comfortably accommodates cutters up to 110mm for deep broaching. It also accepts the VersaDrive Rapid-Lock Weldon Adapter with VersaDrive tooling, opening up 1,000s of time saving solutions from the whole VersaDrive system.

Technical Specifications

CUTTER SIZE RANGE	12 - 40mm TCT
MAX CUTTER LENGTH	110mm
TWIST DRILL CAPACITY	16mm
COUNTERSINKING	25mm
REAMING	12mm
LENGTH	264mm
WIDTH (Inc Handles)	180mm
HEIGHT (Min-Max)	360 - 440mm
STROKE	145mm
WEIGHT	10.5 kg
MAGNET (L X W)	160 x 80mm
MAGNETIC ADHESION	1500 kgs
MOTOR POWER	1150w
SPEED RPM (No Load)	600 RPM
SPINDLE	19.05 mm (3/4") Weldon
COOLANT SYSTEM	Gravity Oil Fed
WARRANTY	2 Year (When registered)

MARKET LEADING PERFORMANCE

Part No	Contents
803046-110	HMT MAX40V Magnetic Drill - 110V
803046-230	HMT MAX40V Magnetic Drill - 230V