


Integrated lubricant system and feed hose



**Technical Specifications**

CUTTER SIZE RANGE	12-40mm
MAX CUTTER CAPACITY	40mm
TWIST DRILL CAPACITY	13mm
LENGTH	310mm
WIDTH	135mm
HEIGHT	180mm
STROKE	40mm
WEIGHT	10.8kg
MAGNET (L x W x H)	160x80x37mm
MAGNETIC FORCE	1200kg
MOTOR POWER	1050W
TOTAL POWER	1100W
SPEED RPM (No Load)	700RPM
SPINDLE	19.05mm 3/4" Weldon
COOLANT SYSTEM	Gravity Oil Fed
WARRANTY	1 Year



The new HMT RTQ40 is a low profile Magnet drill for tight access applications, being designed to fit into any space greater than 180mm. Suitable for use with any standard broaching cutters while optimised to work with the high-performance CarbideMax 40 cutters.

- Ratchet drive can be mounted on either side of the machine.
- Powerful motor and magnet gives excellent stability.
- Quick-change 19.05mm 3/4" arbor for all standard broaching cutters

Each machine comes in a plastic case with hex keys, restraint strap, ratchet, and removable coolant system.

**IDEAL FOR TIGHT ACCESS APPLICATIONS**

Part No	Contents
803084-110	HMT RTQ40 Low Profile Magnetic Drill 110V
803084-230	HMT RTQ40 Low Profile Magnetic Drill 230V