The HMT V100T offers high performance, low maintenance industrial drilling with an all-day broaching capacity up to 100mm diameter.

Its powerful forward /reverse, variable speed, geared Eibenstock motor will tap holes up to M30 and can be used with the VersaDrive [®] blind hole tapping system up to M30. The V100T is also fully rated for reaming and countersinking. Supplied with a coolant fed arbor.



FEATURES & BENEFITS

- All-day broaching capability up to 100mm diameter
- Forward and reverse
- Variable speed motor
- Variable Torque control

TECHNICAL SPECIFICATIONS

CUTTER SIZE RANGE 12 - 100mm TCT MAX CUTTER CAPACITY 100mm TCT MAX CUTTER I FNGTH 200mm TWIST DRILL CAPACITY 32mm COUNTERSINKING 55mm **PEAMING** 26mm MAX TAP CAPACITY M30 LENGTH 345mm WIDTH (Inc Handles) 240mm HEIGHT (Min-Max) 450 - 730mm STROKE 280mm WEIGHT 24.5 kg MAGNET (L X W) 220 X 115mm MAGNETIC ADHESION 2200 kgs MOTOR POWER 1800w **TOTAL POWER** 1900W

SPEED RPM (No Load)
SPINDLE
ARBOR
COOLANT SYSTEM
WARRANTY

SO - 140 / 200 - 470
MT3
AR9,05 mm (¾") Weldon
Gravity Oil Fed
2 Year (When registered)



| • |
|---|
| , |
| |

| Part No | Contents |
|--------------|---------------------------------|
| 850100-P-110 | V100T Magnetic Drill Kit - 110v |
| 850100-P-230 | V100T Magnetic Drill Kit - 230v |





