

<b>GIORGIO GRAESAN</b> and Friends	DATASHEET	Code	TDSOROPURO_00
	<b>ORO PURO</b>	Revision	00
		Date	08/01/2024

#### 1. DESCRIPTION

It is a water-based decorative finish with **Metal Powders and Resins**, which reproduces a **GOLD** effect even on large surfaces.

#### 2. USE

It can be applied onto lime products such as SEGUI IL TUO ISTINTO and MARMORINO 2020 or onto acrylic base coats. It can be applied using a sponge, brush, roller or even a steel trowel depending on the effect to be obtained. Excellent gloss, coverage, adhesion and washability can be obtained with just one coat.

#### 3. SUBSTRATE PREPARATION

Ideal as a finish to be applied directly onto PIETRA SPACCATA, PIETRA ZEN, PIETRA BAMBOO, PIETRA LEVIGATA or MARMORINO 2020.

In the case of other surfaces, proceed with skimming and smoothing with plaster, insulate with an insulating base coat, then apply ORO PURO.

#### 4. APPLICATION METHOD

The product adapts to many application methods and various tools can be used depending on the finish to be obtained. The ones that can be considered the most common, but which are not intended to be binding, are shown below.

Onto PIETRA SPACCATA, PIETRA ZEN and PIETRA BAMBOO, it can be applied using the PE3 brush; if deemed appropriate, the PE7 sponge can be used when the product is still fresh to even out the application and make the surface more reflective.

On smooth finishes such as PIETRA LEVIGATA and MARMORINO 2020, apply with a PE13 roller and then use the KIT/NUDO stainless steel trowel to flatten, even out and make the surface more reflective.

#### 5. TOOL CLEANING

Cleaning of the tools should be performed immediately after use with water.

#### 6. PROTECTION AND CLEANING

The product is already washable without any additional protection, using LATTE DETERGENTE (50 ml diluted in 1 litre of water).

#### 7. SAFETY INDICATIONS AND HAZARD IDENTIFICATION.

The product does not require labelling in accordance with current regulations. Use the product according to current hygiene and safety regulations. After use do not disperse the containers in the environment. Allow the residues to dry well and treat them as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show the healthcare operator the container or label. Do not dispose of residue in sewers, waterways and soil.

For further information see the safety datasheet available on the website: [www.giorgiograesan.it](http://www.giorgiograesan.it)

<b>GIORGIO GRAESAN</b> and Friends	DATASHEET	Code	TDSOROPURO_00
	<b>ORO PURO</b>	Revision	00
		Date	08/01/2024

TECHNICAL SPECIFICATIONS: APPLICATION	
Dilution	Product ready for use.
Mixing	Always mix before use
Colouring	GOLD base
Tools	PE3 Brush - PE13 Roller – PE7 Sponge – KIT/NUDO Trowel
Primer	
Conditions of application	From +10°C to +30°C with relative humidity <85%
Number of coats	1
Drying time	6 – 8 hours at 20°C
Curing time	18 – 24 hours at 20°C
Protective coating	
Washability	Complete washing with LATTE DETERGENTE if protected with VETRO

TECHNICAL SPECIFICATIONS: CONSUMPTION	
ORO PURO	10 sqm/litre but it varies depending on the surface

TECHNICAL SPECIFICATIONS: PRODUCT	
Composition	Acrylic copolymer in water emulsion, additives, metallic fillers
Specific weight	1.10± 0.05 Kg/litre
Ph	>8.0 – 8.5 after 30 days
EU limit value (Dir. 2004/42/EC) Cat. A/l: paints for decorative effects (water-based): 200 g/l	Maximum VOC content: 4.85% - 53.35 g/l
Storage conditions	Store in a tightly closed paint bucket, even after use and after having cleaned the sides and lid of the bucket, keep in a cool and dry place within the temperature range of + 5°C and + 30°C.
Packaging	62 ml – 750 ml

Giorgio Graesan & Friends guarantees that the information on this datasheet is provided to the best of its experience and technical and scientific knowledge, however it cannot assume any responsibility for the results obtained with its use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for the specific case. This document cancels and replaces each previous datasheet. For further technical information contact **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.