

## Velatura Silossanica



### TECHNICAL DATA VELATURA SILOSSANICA

Issued on 03/12/2013 - Rev. n. 1 of 05.09.2023

### FEATURES AND USES

semi-opaque finish for interiors and exteriors based on acrylic-siloxane emulsion, ancient decorative effect. Applicable both on smooth support that rough, either mineral or synthetic. Applied to the outside it allows to obtain a pleasing light colors dark antique effect that goes to embellish and protect the facade, guaranteeing an exceptional water repellency while maintaining unchanged the permeability of the media steam. Inside it can be applied guaranteeing a perfect washability and exceptional aggression bacterial resistance. Its flexibility decorative antique effect and its exceptional endurance performance rank VELATURA SILOSSANICA site as a product for facades in historic centers.

### COMPOSITION

Emulsion acrylic-siloxane, photostable pigments, additives.

### PREPARING THE SURFACE

Sanding, dusting, any imperfections with stucco in paste and / or powder form and apply a suitably diluted universal Fissativo with water according to the absorption of the substrate. Allow to dry for at least 4 hours and apply one or two coats of PRIMER PLUS white or slightly pigmented, suitably diluted, interspersed between a hand and the other at least 4-5 hours.

### APPLICATION

proceed with the drafting of VELATURA SILOSSANICA of the desired color with a brush, and quickly, product is still fresh, finish with wool glove with non-continuous circular movements.

### WARNINGS:

Do not apply on damp walls or where there has been ascertained rising damp, do not apply in foggy or near rains. Apply with a temperature between 5 and 30 ° C.

### TECHNICAL DATA

SPECIFIC WEIGHT: 1,040 +/- 5%

COLOR: as per folder

VISCOSITY '': 200 ''- 250'' Ford Cup 4

YIELD: 9-10 m<sup>2</sup> / Lt in one coat

DILUTION: ready for use

PACKAGE: polyethylene containers Lt. 2,5 - 1 Lt.

DRYING: tack free 1 h, in depth 24h at 20 ° C

TEMPERATURE OF APPLICATION: between 7 ° C and 30 ° C

APPLICATION: Brush, roller, or spray

STORAGE: 24 months in unopened packs away from temperature changes

### Nikkolor Italia s.r.l.

V.le Vittorio Veneto, 186 - 96014 Florida (SR)

+39 0931 941789 - www.nikkolor.net



The use of coloring pastes not supplied by Nikkolor Italia can compromise not only the aesthetic appearance but above all can significantly alter the performance of the product itself.

The data contained in these technical sheets refer to laboratory tests. The indicated indications and methods may be subject to changes over time according to possible improvements in production technologies. The application of the products takes place beyond our control as we cannot directly intervene on the conditions of the construction sites and on the execution of the works. All indications are of a general nature, they do not bind our company in any way and therefore the responsibility falls exclusively on the customer. A preventive test of the product is recommended in order to verify its suitability for the intended use. Our technical service is available to provide additional information.