

OPAKO

Water-based one component matt topcoat for CalceTerra

Product characteristics and uses

OPAKO is a one component water-based topcoat with excellent performance.

Possible Uses

OPAKO is used as protective transparent topcoat on walls over which CALCETERRA has been applied where you need to improve surface protection and performance.

Surface preparation

After CALCETERRA has been applied and the walls are completely dry, OPAKO may be applied.

Product preparation

OPAKO is a one component, ready to use product. Mix the tin before the use.

- *Hardening*: one component product
- *Dilution*: about 20% with water

Application Method

OPAKO is applied as 2 or 3 coats by sponge, roller or brush.

Colour

OPAKO is a transparent matt topcoat (about 0 Gloss)

Application and storage conditions

- *Application temperature*: between +15°C and +35°C
- *Storage temperature*: between +5°C and +35°C
- *Cleaning tools*: use warm water



Technical Data Sheet n° C 504.20

pag. 2 of 2

Ver. 1.2/0520

Technical Features

TECHNICAL DATA	UNIT of MEASUREMENT	VALUE
Specific weight at 20°C	Kg/L	1,05 ± 0,02
Dry remainder	%	37 ± 1
DIN 4 viscosity	s	150 ± 10
Mixing ratio	-	One component product
Dilution	-	Max 20% with water
Approximate covering	Kg/sqm	0.1-0.15 Kg/sqm (2 coats)

Reaction Times (e.g. temperature 20°C and 50% relative humidity)

- *Dust dry*: about 15-20 minutes
- *Touch dry*: about 1 hour

Packaging

- 1 Kg
- 5 Kg

For further information contact the technical office Gruppo GANI at the number +39.031.905163.

The information contained in this technical card are based on the common experience in the sector, without specific implicit or explicit guarantee.

The application and the use of our products take place outside our control possibilities and so those fall down under the exclusive responsibility of the user.

ELEKTA is a division of:

GRUPPO GANI S.r.l. - Via Vivaldi, 4 22071 Cadorago (CO) Tel: (+39) 031 905163

www.elektacalce.it - gruppogani@gruppogani.com