

| | | | |
|---------------------------------------|-----------------------|----------|------------|
| GIORGIO GRAESAN and Friends | DATASHEET | Code | TDS1027_00 |
| | VETRO SATINATO | Revision | 00 |
| | | Date | 20/09/2021 |

1. DESCRIPTION

VETRO SATINATO is protective finish based on acrylic polymers, transparent with a satin finish. Soft and silky to the touch , it is water based and creates a waterproof finish, considerably increasing washability and resistance to stains and dirt.

2. USE

It is suitable for application on internal walls of bathrooms, kitchens or other locations that require protection from water. It is suitable for the interior of shower stalls or other locations in direct contact with water.

Once dry, VETRO SATINATO, seals the surface giving a satin and compact appearance.

It can also be used as an insulating primer before applying IPER VETRO on surfaces containing our lime-based products.

3. SUBSTRATE PREPARATION

The surface on which it is applied must be clean, dry, and adherent.

4. APPLICATION METHOD

VETRO SATINATO is ready to use.

The substrate must be **completely dry** for at least 24 hours before applying the product. If applied on surfaces while still wet, it tends to whiten and its protective action is reduced.

Apply the first coat generously until saturated using a PE10 brush, avoiding any dripping.

After 4-6 hours apply the second coat smoothly and evenly, again using a PE10 brush.

On smooth surfaces, a PE3 brush can be used for the second coat, making it easier to avoid brush marks.

The milky appearance and brush marks that may appear during application will disappear as the product dries.

Go over the corners or other hard-to-reach points with a brush, especially where surfaces join.

Upon completion, seal the edges in contact with other surfaces (shower tray, taps, kitchen counters) with suitable sealant so as to avoid water penetration, which could result in the formation of halos or cracks.

5. TOOL CLEANING

Rinse tools with water.

6. CLEANING THE FINISHED PRODUCT

Clean with LATTE DETERGENTE (50 ml of LATTE DETERGENTE in 1 litre of water).

| | | | |
|---------------------------------------|-----------------------|----------|------------|
| GIORGIO GRAESAN and Friends | DATASHEET | Code | TDS1027_00 |
| | VETRO SATINATO | Revision | 00 |
| | | Date | 20/09/2021 |

7. SAFETY INDICATIONS AND HAZARD IDENTIFICATION

The product does not require labelling in accordance with current regulations. Use and store according to current hygiene and safety regulations. After use, do not dispose the containers in the environment. Allow the residues to dry well and treat them as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show the healthcare operator the container or label. Do not dispose of residue in drains, sewers, waterways and soil. For further information, see the safety datasheet available on the website: www.giorgiograesan.it

| TECHNICAL SPECIFICATIONS: APPLICATION | |
|---------------------------------------|---|
| Dilution | Product ready for use |
| Mixing | Always mix before use |
| Colouring | Not applicable |
| Tools | PE 10 brush and/or PE 3 brush |
| Primer | Not required |
| Conditions of application | From +10°C to +35°C with relative humidity <85% |
| Number of coats | 2 |
| Drying time | Each coat dries in 4 – 6 hours at 20°C |
| Curing time | 24 hours at 20°C |
| Washability | Fully washable with LATTE DETERGENTE |

| TECHNICAL SPECIFICATIONS: CONSUMPTION | |
|---------------------------------------|--|
| VETRO SATINATO | 13 m ² /litre for the two coats |

| TECHNICAL SPECIFICATIONS: PRODUCT | |
|--|--|
| Composition | Acrylic copolymer in aqueous emulsion |
| Specific weight | 1.01± 0.03 Kg/litre |
| Ph | 9.2 |
| EU limit value (Dir. 2004/42/EC) Cat. A/l: paints for decorative effects (water-based): 200 g/l | Maximum VOC content 13.92 g/l |
| Storage conditions | Store in a tightly closed paint tub even after use and after having cleaned the sides and lid of the tub. Keep in a cool and dry place within the temperature range of + 5°C and + 30°C. |
| Packaging | 1 and 2.5 litres |

Giorgio Graesan & Friends guarantees that the information on this datasheet is provided to the best of its experience and technical and scientific knowledge, however it cannot assume any responsibility for the results obtained with its use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for the specific case. This document cancels and replaces each previous datasheet. For further technical information contact **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.