



## SPECS

FRAME	
SIZES	SM / MD / LG / XL
COLOUR	BLACK
FRAME	SERIES 2 CUSTOM BUTTED AND HYDROFORMED 6061 ALLOY TUBESET
FORK	UD CARBON FORK / TAPERED STEERER / MUDGUARD EYELETS / 12X100
REAR-SHOCK	N/A
HEADSET	PRESTINE PT-1860
COMPONENTS	
HANDLEBARS	RACEFACE RIDE FLAT / 710MM
STEM	SARACEN ALLOY 31.8 / 70MM
GRIPS	ODI ELITE MOTION
SADDLE	SARACEN CUSTOM CRMO
SEATPOST	SARACEN ALLOY / 30.9MM
PEDALS	N/A
DRIVE TRAIN	
SHIFTERS	DEORE M6000 / 1 X 10 SPEED
REAR-DERAILLEUR	SHIMANO DEORE M6000 / 1 X 10 SPEED
FRONT-DERAILLEUR	N/A
CHAINSET	PROWHEEL / 42T
CHAIN	KMC X10
CASSETTE	SHIMANO DEORE / 10 SPEED / 11-42T
BRAKES	SHIMANO MT-200
BRAKE-LEVERS	SHIMANO MT-200
WHEELS	
RIMS	JALCO / 32H / 27.5"
HUBS	FORMULA 12 X 100 / 12 X 142
SPOKES	DOUBLE-BUTTED STAINLESS STEEL
TYRES	MAXXIS RAMBLER / SILSHIELD / TR / 27.5 X 47C

## FEATURES

- Series 2 custom butted and hydroformed 6061 alloy tubeset / IS42-IS52 tapered headtube / 12 x 142mm dropout for on- and off-road adventures
- Fork: UD carbon fork / tapered steerer / mudguard eyelets / 12x100
- Drivetrain: Shimano Deore / 10 Speed, 11-42T
- Brakes: Shimano MT-200
- Components: Raceface Ride Flat bar and 70mm stem, Maxxis Rambler 650 x 47C tyres

## GEOMETRY

SIZE	S	M	L	XL
SEAT TUBE (MM)	490	520	550	580
TOP TUBE (MM)	560	585	610	635
REACH (MM)	385	404	424	443
STACK (MM)	572	590	609	628
HEAD TUBE (MM)	135	155	175	195
HEAD ANGLE (°)	70.5	70.5	70.5	70.5
SEAT ANGLE (°)	73	73	73	73
CHAINSTAY (MM)	425	425	425	425
BB DROP (MM)	68	68	68	68
BOTTOM BRACKET (MM)	271	271	271	271
WHEELBASE (MM)	1044	1071	1097	1123
HEAD SET	44ZS/56ZS	44ZS/56ZS	44ZS/56ZS	44ZS/56ZS
LOWER STACK HEIGHT (MM)	0.9	0.9	0.9	0.9
AXLE TO CROWN (MM)	400	400	400	400
OFFSET (MM)	50	50	50	50

The image above is for illustration purposes only. Saracen reserves the right to change spec, colour, features and price without prior warning.