



SPECS

FRAME	
SIZES	SM / MD / LG / XL
COLOUR	RED
FRAME	SERIES 3 CUSTOM BUTTED AND HYDROFORMED 6013 ALLOY FRONT TRIANGLE AND SWINGARM / 203MM TRAVEL
FORK	ROCKSHOX BOXXER SELECT RC / 203MM TRAVEL
REAR-SHOCK	MARZOCCHI BOMBER CR
HEADSET	PRESTINE PTF13
COMPONENTS	
HANDLEBARS	RACEFACE CHESTER 35 / 780MM / 35MM
STEM	RACEFACE CHESTER 35 / DIRECT MOUNT
GRIPS	ODI ELITE MOTION
SADDLE	SARACEN CUSTOM DH CRMO MTB
SEATPOST	RACEFACE CHESTER / 30.9MM / 325MM
PEDALS	ALLOY MTB / SEALED BEARINGS / REPLACEABLE PINS
DRIVE TRAIN	
SHIFTERS	SRAM GX DH 7
REAR-DERAILLEUR	SRAM GX DH 7
CHAIN DEVICE	MRP G4 CS
CHAINSET	SAMOX / SARACEN CUSTOM / 36T / 165MM
CHAIN	KMC II
CASSETTE	SRAM PG 720 DH 7 SPEED
BRAKES	SHIMANO MT520 203/203MM
BRAKE-LEVERS	SHIMANO MT501
WHEELS	
RIMS	JALCO / 32H / 27.5"
HUBS	FORMULA BOOST 20 X 110 SEALED BEARING 32H FRONT / KT 12 X 150 SEALED BEARING 32H REAR
SPOKES	DOUBLE-BUTTED STAINLESS STEEL
TYRES	MAXXIS DHR11 / 27.5 X 2.4 / DH CASING

FEATURES

- Series 3 custom butted and hydroformed 6013 alloy front triangle and swingarm, signature TRL suspension design, 12 x 150mm dropout system, 203mm travel
- Shock: Marzocchi Bomber CR, Rebound Adjust, 241 x 76
- Fork: Rockshox BoXXer Select RC, 203mm travel, DebonAir, low speed compression, rebound adjust, 20 x 110, Maxle Stealth DH
- Drivetrain: Sram GX DH 7
- Brakes: Shimano MT520 calipers with MT501 Deore levers
- Components: Raceface Chester 35 bar and direct mount stem, ODI grips, Raceface seatpost

GEOMETRY

SIZE	S	M	L	XL
ST	400	400	400	400
TT	593	613	630	653
REACH	420	440	460	480
STACK	602	602	602	611
HT	115	115	115	125
HA	63.0	63.0	63.0	63.0
SA	74.0	74.0	74.0	74.0
CS	440	440	440	440
BB	1.5	1.5	1.5	1.5
WB	1226	1246	1266	1294

The image above is for illustration purposes only. Saracen reserves the right to change spec, colour, features and price without prior warning.

MYST AL

TECHNICAL INFORMATION

SARACEN

MODEL	MYST AL
FRAME MATERIAL	AL-6013
REAR TRAVEL	200MM
SHOCK LENGTH / STROKE	241MM X 76MM
SHOCK SAG	19MM – 23MM
SAG EYE TO EYE	222MM – 218MM
PIGGY BACK COMPATIBLE	YES
FRAME SHOCK BUSHING	22MM X 8MM
LINKAGE SHOCK BUSHING	22MM X 10MM
RECOMMENDED / MAX FORK LENGTH	581MM / +20MM
OFFSET	44-52MM
RECOMMENDED / MAX FORK TRAVEL	27.5" DC 200MM
MAXIMUM TYRE	27.5" X 2.6"
BRAKE MOUNT TYPE	IS160
MAX REAR ROTOR	200MM
SEAT POST	30.9MM
SEAT COLLAR	34.9MM
BOTTOM BRACKET TYPE	BSA83
ISCG	05
CRANK CHAINLINE	SUPER BOOST
MAX CHAIN RING	38T
REAR HUB TYPE	12 X 150



MARZOCCHI SUSPENSION

SETUP GUIDE

Marzocchi CR / 9.5 x 3.0

RIDER WEIGHT (LBS)	RIDER WEIGHT (KGS)	PRESSURE (PSI)	SAG (%)	SAG (MM)	LSR (CLICKS)	LSC (CLICKS)
90	41	250	25-30%	19-23MM	12-13	15-16
110	50	275	25-30%	19-23MM	11-12	15-16
130	59	300	25-30%	19-23MM	10-11	14-15
150	68	325	25-30%	19-23MM	9-10	14-15
170	77	350	25-30%	19-23MM	8-9	13-14
190	86	375	25-30%	19-23MM	7-8	13-14
210	95	400	25-30%	19-23MM	6-7	12-13
230	104	425	25-30%	19-23MM	6-7	12-13

NOTE: ALL CLICKS ARE FROM FULLY CLOSED POSITION

The image above is for illustration purposes only. Saracen reserves the right to change spec, colour, features and price without prior warning.