

Printing date: 30.05.2022 Revision: 2 / 22.11.2021 Page 1 / 6

### 1. Identification of the product and of the company/undertaking

Trade name: MAGNUM® fillet weld special flap disc

Supplier: Gerd Eisenblätter GmbH

Jeschkenstraße 12d 82538 Geretsried

Phone: + 49 (0) 8171 / 9082 - 010

**Emergencies:** +49 (0) 8171 / 9082 – 010

#### 2. Hazards identification

#### 2.1. Classification

Not applicable

Abrasives are articles and not dangerous substances or mixtures according to the Regulation (EC) No. 1272/2008. See also section 8 and 16.

#### 2.2. Label elements

Abrasives are articles and not dangerous substances or mixtures and therefore no labelling is required according to the Regulation (EC) No. 1272/2008.

### 2.3. Other hazards

Not known.

# 3. Composition / information on ingredients

The product contains the following ingredients which are classified according to Regulation (EC) Nr. 1272/2008 or for which a community occupational exposure limit value exists:

Substance	EC-No.	CAS-No.	REACH Registration No.	Conc. (%)	Classification acc. to. Regulation (EC) No. 1272/2008 (CLP)	
					Hazard classes / Hazard categories	Hazard statements
Cryolite (sodium aluminium fluoride)	237-410-6	13775-53-6	01-2119511565-43	1 - 9 %	Acute toxicity Cat. 4	H332
					Reproductive toxicity Lact.	H372
					STOT RE 1	H362
					Aquatic Chronic 2	H411

(For full text of H-phrases see section 16.)



Trade Name: MAGNUM® fillet weld special flap disc Page 2 / 6

#### 4. First aid measures

See also section 8 and 16.

### 4.1. Description of first aid measures

Inhalation : Not possible, due to the form of the products.

Skin contact : No harmful effects known.

Eye contact : Not possible, due to the form of the products.

Ingestion : Not likely, due to the form of the product; if necessary contact physician.

Note to physician : Not available.

### 4.2. Most important symptoms and effects, both acute and delayed

Not known.

## 4.3. Indication of any immediate medical attention and special treatment needed

Not relevant. Treat symptomatically.

# 5. Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: water, foam, sand, powder or CO<sub>2</sub> as appropriate for surrounding materials.

# 5.2. Special hazards arising from the product

Toxic fumes may occur. Use respiratory protective equipment.

# 5.3. Advice for fire fighters

Extinguishing materials should be selected according to the surrounding area.

## 6. Accidental release (Spill containment measures)

Not applicable.

# 7. Handling and storage

Follow instructions of grinding machine manufacturers and the relevant national regulations. In addition, observe the safety recommendations of the manufacturer.

Store abrasives in dry, frost-free conditions avoiding wide variations in temperature. Ensure they are properly protected and supported to prevent damage und distortion. Coated abrasives should be stored at 18-22 °C, 45-65 % relative humidity.



Trade Name: MAGNUM® fillet weld special flap disc Page 3 / 6

# 8. Exposure controls / personal protection

# 8.1. Control parameters

Before grinding it is recommended to perform a risk assessment and to use personal protection equipment accordingly.

Occupational exposure limit values and / or biological limit values.

Keep exposure to the following components under surveillance. (Observe also the regional official regulations)

Limit value to a			Occupational limit value					Course	
Limit value type (country of origin)	Substance	EC-No.	CAS-No.	Long	term		Short term	Peak limit	Source, Remark
(country or origin)				mg/m <sup>3</sup>	ml/m <sup>3</sup>	mg/m <sup>3</sup>	ml/m³ (ppm)		Keman
WEL (UK)	Cryolite	237-410-6	13775-53-6	2.5 *					HSC (fluorides, inorganic as F)
European Union	Cryolite	237-410-6	13775-53-6	2,5					

<sup>\*</sup> Valid for UK, other countries: observe national values

Note: Hazardous dust of the workpiece material may be generated during grinding and / or sanding operations. National regulations for dust exposure limit values have to be taken into consideration.

#### 8.2. Exposure controls

- 8.2.1. Individual protection measures
- 8.2.1.1. Respiratory protection: Use respiratory protective equipment (Type depends on specific application and material being ground)
- 8.2.1.2. Hand protection: Wear protective gloves
  (Type depends on specific application and material being ground)
- 8.2.1.3. Eye protection: Wear protective goggles or face shield (Type depends on specific application and material being ground)
- 8.2.1.4. Hearing protection: Use hearing protection (Type depends on specific application and material being ground)
- 8.2.1.5. Body protection: Use protective clothing (Type depends on specific application and material being ground)

### 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: solid

Colour: according to the type of product

Solubility in water: not measured

#### 9.2. Other information

None.



Trade Name: MAGNUM® fillet weld special flap disc Page 4 / 6

# 10. Stability and reactivity

#### 10.1. Reactivity

Coated abrasives are stable when handled or stored correctly.

### 10.2. Chemical stability

No decomposition in normal use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4. Conditions to avoid

Coated Abrasives are stable when handled or stored correctly.

### 10.5. Incompatible materials

No dangerous reactions known.

#### 10.6. Hazardous decomposition products

At temperatures exceeding 250°C hazardous or toxic decomposition products may be generated.

### 11. Toxicological information

# 11.1. Information on toxicological effects

No toxicological effects if inhaled or swallowed or with eye or skin contact are known. See also section 8.

# 12. Ecological information

### 12.1. Toxicity

No effects known.

#### 12.2. Persistence and degradability

No biodegradable potentials known.

### 12.3. Bioaccumulative potential

No potentials known.

# 12.4. Mobility in soil

No potentials known.

#### 12.5. Results of PBT and vPvB assessment

Not relevant.

# 12.6. Other adverse effects

No effects known.



Trade Name: MAGNUM® fillet weld special flap disc Page 5 / 6

### 13. Disposal considerations

#### 13.1. Waste treatment methods

13.1. Product

Follow national and regional regulations.

**O** Due to the ingredients and properties disposal as non hazardous waste (2000/532/EC) is possible if no hazardous materials are added to the abrasives. (EWC – Nr. 120121),

**X** Due to the ingredients and properties disposal as hazardous waste (2000/532/EC) (EWC – Nr. 120120)

13.2. Packing

Follow national and regional regulations.

#### 14. Transport information

The product is not covered by international regulation on the transport of dangerous goods.

#### 15. Regulatory information

#### 15.1. Safety, health and environmental regulations / legislation specific for the product

No specific labelling requirements under respective EC directives.

#### 15.2. Chemical safety assessment

Not relevant.

# 16. Other information

#### Literature and data sources

REACH Regulation (EC) Nr. 1907/2006 Regulation (EC) N° 1272/2008 Directive 98/24/EC Directive 2000/39/EC Directive 75/324/EEC Decision 2000/532/EC

Transport regulations according to ADR, RID und IATA.

# Hazard statements referred to in section 2 and 3 According to Regulation (EC) N° 1272/2008:

#### Cryolite, hazard statements

H 332 Harmful if inhaled

H 372 May cause damage to organs (lung, skeleton) to prolonged or repeated exposure

H 362 May cause harm to breast-fed babies

H 411 Toxic to aquatic life with long lasting effects



Trade Name: MAGNUM® fillet weld special flap disc Page 6 / 6

Substance: Fluoride (inorganic as F) CAS No. 16984-4

Substance Fluoride (inorganic as F)
CAS No. 16984-48-8

	Limit value - Eight hours		Limit value - Short term
	ppm	mg/m³	ppm
Austria		2,5 inhalable aerosol	
<u>Belgium</u>		2,5	
<u>Denmark</u>		2,5	
European Union		2,5	
France		2,5	
Germany (AGS)		1 (1)(2)	
Germany (DFG)		1 (1)(2)	
<u>Hungary</u>		2,5	
Ireland		2,5	
<u>Italy</u>		2,5	
<u>Latvia</u>		2,5	
Poland		1	
Romania		2,5	
Singapore		2,5	
<u>Spain</u>		2,5	
Sweden		2	
Switzerland		1 inhalable aerosol	
Turkey		2,5	
USA - OSHA		2,5	
United Kingdom		2,5	

	Remarks
European Union	Bold-type: Indicative Occupational Exposure Limit Value (IOELV) ~ (for references see <u>bibliography</u> )
Germany (AGS)	(1) Inhalable fraction (2) Skin (3) 15 minutes average value
Germany (DFG)	(1) Inhalable fraction (2) Skin (3) 15 minutes average value

<sup>\*(</sup>IFA / GESTIS Stoffdatenbank, Internationale Grenzwerte für chemische Substanzen)

The information given is based on current knowledge. Products are described in term of their safety data. The data does not signify any warranty with regard to the products properties.

The product should only be used for the stated application or applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet.