



TruTool TKA 1500

Technical data

**TruTool TKA 1500
without tool****TruTool TKA 1500 45°
tool****MAXIMUM CHAMFER LENGTHS**

MAXIMUM CHAMFER LENGTH, STEEL 400 N/MM ²	15 mm	15 mm
MAXIMUM CHAMFER LENGTH, STEEL 600 N/MM ²	12 mm	12 mm
MAXIMUM CHAMFER LENGTH, STEEL 800 N/MM ²	10 mm	10 mm
MAXIMUM CHAMFER LENGTH, ALUMINIUM 250 N/MM ²	15 mm	15 mm

MAXIMUM CHAMFER HEIGHTS

MAXIMUM CHAMFER HEIGHT, STEEL 400 N/MM ²	10.6 mm	10.6 mm
MAXIMUM CHAMFER HEIGHT, STEEL 600 N/MM ²	8.5 mm	8.5 mm
MAXIMUM CHAMFER HEIGHT, STEEL 800 N/MM ²	7.1 mm	7.1 mm
MAXIMUM CHAMFER HEIGHT, ALUMINIUM 250 N/MM ²	10.6 mm	10.6 mm

RADII

SMALLEST INNER RADIUS	30 mm	30 mm
SMALLEST BORE HOLE (∅)	55 mm	55 mm

GENERAL

MINIMUM SHEET THICKNESS	3 + hs mm	3 + hs mm
WORKING SPEED	1 m/min - 1.5 m/min	1 m/min - 1.5 m/min
NOMINAL POWER CONSUMPTION	2600 W	2600 W
SPEED DURING IDLE RUN	6700 1/min	6700 1/min

WEIGHT

WEIGHT WITHOUT CABLE	10 kg	10 kg
----------------------	-------	-------