

Product data sheet

Characteristics

5085EDLW-OM

Wall Plate, C-Bus, Saturn, Enhanced Dynamic Labelling Technology, 5 keys, white grid, ocean mist



Main

| | |
|---------------------------|--------------|
| Range | C-Bus |
| Product brand | Clipsal |
| Product name | C-Bus Saturn |
| Product or component type | Wall plate |
| Device application | Control |

Complementary

| | |
|-----------------------------|--|
| Colour | Cover plate: ocean mist Grid: white |
| Provided equipment | Mounting plate Flying lead |
| Control type | 5 x push-button dual-action |
| Local signalling | Status: LED (tri-colour) on push-button |
| Switch application | Lighting Timer Audio Blind control Fan speed control Scene control On/Off switching Shutter control Dimming up/down control Page navigation |
| Local display | Backlit LCD display |
| Display type | Colour TFT display |
| Display size | 2.8 inch |
| Messages display capacity | Up to 4 pages |
| Information displayed | Load type Temperature Power Date Time Operating mode |
| Number of outputs | 16 in 4 page option 5 in 1 page option |
| Function of module | Proximity sensor monitoring wake-up |
| Communication port protocol | C-Bus - 2 wires |
| [Us] rated supply voltage | 15...36 V: DC |
| Maximum supply current | 32 mA |
| Material | Glass |
| Connector type | Mini USB port (rear) Socket (rear) for C-Bus |
| Function available | Firmware update by USB |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------------------------|---------------------------|
| User language | Multi-language |
| Product compatibility | LAN cable Cat. 5e |
| Electrical connection | Flying lead |
| Clamping connection capacity | 0.2...1.5 mm ² |
| Fixing mode | By screws |
| Mounting support | Wall |
| Width | 77 mm |
| Height | 123 mm |
| Depth | 35 mm |
| Embedding depth | 23.5 mm |
| Colour code | OM |







Environment

| | |
|---------------------------------------|-----------|
| IP degree of protection | IP20 |
| Ambient air temperature for operation | 5...45 °C |
| Product certifications | CE RCM |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 307.1 g |
| Package 1 Height | 8.0 cm |
| Package 1 width | 11.1 cm |
| Package 1 Length | 15.6 cm |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 240 |
| Package 2 Weight | 97.082 kg |
| Package 2 Height | 103.0 cm |
| Package 2 width | 66.0 cm |
| Package 2 Length | 67.5 cm |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 8 |
| Package 3 Weight | 2.903 kg |
| Package 3 Height | 20.6 cm |
| Package 3 width | 22.5 cm |
| Package 3 Length | 33.0 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |