

Acti9 PowerTag Link HD - Wireless to Modbus TCP/IP Concentrator

A9XMWD100

viain	۱
-------	---

Range of product	Acti9
Product name	Acti9 PowerTag Link HD
Product or component type	Smart communication module
Device short name	PowerTag Link HD
Application type	Basic energy metering E Improved load monitoring E, U, I, P, Pf Load alarming
Number max of connected devices	Up to 100 wireless devices
Maximum supply current	2 A
[Us] rated supply voltage	110230 V AC +/- 15 %
Connectivity to devices	Wireless energy sensor
Communication service	Ethernet Modbus TCP/IP server Web server
Web server	Embedded web page BMS controller compatible
Transmission support medium	Radio frequency 2.42.4835 GHz PowerTag 100
Web services	Web page

Complementary

Application specific I/O	Pulse totalising counter
Power consumption in VA	5 VA
Immunity to microbreaks	10 ms
Reset	Factory reset on front face
Local signalling	Product status: 1 LED (green, orange and red) Ethernet status (LAN ST): 1 LED (green, orange and red)
Mounting position	Horizontal/vertical on DIN rail
Colour	White (RAL 9003)
Location of connection	Upstream
Overvoltage category	III
9 mm pitches	6 useful
Height	85 mm

Width	54 mm	
Depth	67.5 mm	
Net weight	133 g	
Range compatibility	PowerTag wireless energy sensor	
Commissioning interface	Web page ECOREACH	
Compatibility code	Acti9 PowerTag Link HD	
Environment		
IP degree of protection	IP20 conforming to IEC 60529	

IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	2
Tropicalisation	2
Relative humidity	93 % at 40 °C
Operating altitude	02000 m
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-4085 °C

Packing Units Unit Type of Package

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	187.0 g
Package 1 Height	8.2 cm
Package 1 width	6.8 cm
Package 1 Length	11.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Weight	7.19 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov